



Stay rope



## Spiral Strand 1x19 Stainless

### Product information



**Typical applications:** Wire rope for rigging, stays and controls.

**Design:** Right- or left-handed.

**Rope construction:** 1x19

**Material:** AISI 316

**Marking:** According to standard

**Standard:** EN 12385-10  
*except material*

**Fill factor:** 0.76

Part code	Rope diameter mm	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay	Min. breaking force kN	Steel area mm <sup>2</sup>	Lubrication	Weight kg/100m
01.S52019010D	1	1,570	Stainless	S	0.82	-	No-Lube	0.5
01.S52019020D	2	1,570	Stainless	S	3.3	-	No-Lube	2
01.S52019030D	3	1,570	Stainless	S	7.42	-	No-Lube	4.5
01.S52019040D	4	1,570	Stainless	S	13.2	-	No-Lube	7.9
01.S52019050D	5	1,570	Stainless	S	20.6	-	No-Lube	12.4
01.S52019060D	6	1,570	Stainless	S	29.7	-	No-Lube	17.8
01.S52019070D	7	1,570	Stainless	S	40.4	-	No-Lube	24.3
01.S52019080D	8	1,570	Stainless	S	52.8	-	No-Lube	31.7
01.S52019100D	10	1,570	Stainless	S	82.5	-	No-Lube	49.5
01.S52019120D	12	1,570	Stainless	S	119	-	No-Lube	71.3