



SS 6x36 IWRC

Product information



Stainless steel wire rope.

Design: Cross lay right-handed, alternative design on request.

Rope construction: 6x36 IWRC.

Material: AISI 316/1570 N/mm²

Part code	Rope diameter mm	Tensile strength N/mm ²	Finish	Rope lay	Min. breaking force kN	Steel area mm ²	Lubrication	Weight kg/100m
01.S10265080D	8	1,570	Stainless	sZ	36.6	-	No-Lube	27
01.S10265100D	10	1,570	Stainless	sZ	56.9	-	No-Lube	42
01.S10265120D	12	1,570	Stainless	sZ	80.6	-	No-Lube	60.2
01.S10265130D	13	1,570	Stainless	sZ	94.8	-	No-Lube	70.7
01.S10265140D	14	1,570	Stainless	sZ	109	-	No-Lube	82
01.S10265150D	15	1,570	Stainless	sZ	125.8	-	No-Lube	94.5
01.S10265160D	16	1,570	Stainless	sZ	142	-	No-Lube	107
01.S10265180D	18	1,570	Stainless	sZ	180	-	No-Lube	135
01.S10265200D	20	1,570	Stainless	sZ	221	-	No-Lube	167
01.S10265240D	24	1,570	Stainless	sZ	321	-	No-Lube	241