

## Vacuum Beams AERO-90°

### Product information



moving limits

The standard vacuum lifting beams AERO-90° are designed from robust welded steel, with integrated motor protection switch, which protects the vacuum generator from winding damage. Stepless, smooth swivel from 0°-90° thanks to electric linear drive.

They are typically used for lifting steel and aluminium sheets and plastics.

### Product variants

The AERO-90° vacuum lifter is available in different versions with:

- load capacities from 125 to 1,000 kg
- 4 to 8 suction plates
- 2 to 4 crossbars
- different suction plate diameters, etc.



WLL ton	Model	D mm	L mm	B mm	LG mm	D EH mm	EH mm	Weight kg
0.125	AERO-90° 125/4R/2000	170	2,000	1,000	713	60	1,100	114
0.125	AERO-90° 125/8R/2000	120	2,000	1,000	713	60	1,100	130
0.25	AERO-90° 250/4R/2000	270	2,000	1,000	713	60	1,100	120
0.25	AERO-90° 250/8R/2000	170	2,000	1,000	713	60	1,100	133
0.5	AERO-90° 500/4R/2000	350	2,000	1,000	713	60	1,100	147
0.5	AERO-90° 500/8R/2000	270	2,000	1,000	713	60	1,100	171
1	AERO-90° 1000/8R/2000	350	2,000	1,000	703	60	1,240	218

Blueprint

