



Fall Arrest Block IKAR HWB with Webbing

Product information

Robust, low-maintenance fall arrest device with webbing and swivel. The swivel prevents the webbing from twisting. Internal energy-absorber and hook with fall indicator.

Low weight thanks to extra light plastic housing.

Approved for vertical and horizontal use.

Edge tested: Tested at sharp edges, $R \geq 0,5$ mm
(CNB/P/11.060 2008 sharp edge Type A)

Carabiner: IKAR IKV11 (Lk = 137 mm) Small swivel snap hook (opening \varnothing 25 mm).

The blocks can be delivered with the following approvals: ANSI/ASSE Z 359.14-2014/LE up on request.

Material: Body: Aluminium. - Webbing: Dyneema®

Marking: According to standard, CE-marked

Temperature range: -40°C up to 50°C

Standard: EN 360

Part code	Code	Max. number of persons	Length m	Max load kg	L mm	B, mm	T mm mm	Weight kg
19.0741-HWB1,8	HWB 1.8	1	1.8	136	237	78	60	0.7
19.0741-HWB2	HWB 2	1	2	136	240	84	61	0.9
19.0741-HWB2,8	HWB 2.8	1	2.8	136	273	94	69	1.2
19.0741-HWB3,5	HWB 3.5	1	3.5	136	270	88	64	1.6

Blueprint

