

# Round Sling EXTREEMA® XS



## Product information

The XS round slings are the ultimate solution for lifting loads ranging from 3T to 20T. They offer a cost-effective and reliable alternative to traditional polyester slings. Say goodbye to the hassle of disposal, storage, and transportation costs, and welcome a practical and efficient choice that never compromises safety and quality.

Their lightweight design ensures easy handling and transport, making them a practical choice across various lifting applications. By embracing the XS round slings, industries secure a dependable lifting solution and embark on a sustainable journey, reducing industrial waste and minimizing their environmental footprint.

Extreema XS Slings have massive lifting power in a much smaller size with 78% less weight than polyester round slings and 55% smaller diameter, you can lift on the shackle pin. Slings are 8-10 times lighter than steel wire ropes.

### Features and benefits:

- Saving costs
- D:d ratio of 1:1
- Environmentally friendly
- Light in weight
- Flexible
- Less storage
- Long life cycle
- Access to limited lifting space
- Safer lifting operations
- Improving workflow
- Available in 3t yellow, 5t red, 10t orange, 15t orange and 20t orange
- Available in effective working lengths in the range of 0.5 m up to 16 m
- Standard with RFID

**Material:** HMPE -Dyneema®

**Marking:** According to standard, CE-marked

**Temperature range:** -40 °C and +70 °C

**Standard:** EN 1492-2

*except material*

**Safety factor:** 7:1

Part code	WLL ton	EWL m	Colour
12.20EXHL030005	3	0.5	Yellow
12.20EXHL0300075	3	0.75	Yellow
12.20EXHL030010	3	1	Yellow
12.20EXHL030015	3	1.5	Yellow
12.20EXHL030020	3	2	Yellow
12.20EXHL030025	3	2.5	Yellow
12.20EXHL030030	3	3	Yellow
12.20EXHL030040	3	4	Yellow
12.20EXHL030050	3	5	Yellow
-	3	6	Yellow
12.20EXHL050005	5	0.5	Red
12.20EXHL050010	5	1	Red
12.20EXHL050015	5	1.5	Red
12.20EXHL050020	5	2	Red
12.20EXHL050025	5	2.5	Red
12.20EXHL050030	5	3	Red
12.20EXHL050040	5	4	Red
12.20EXHL050050	5	5	Red
-	5	6	Red
12.20EXHL100015	10	1.5	Orange
12.20EXHL100020	10	2	Orange
12.20EXHL100030	10	3	Orange

12.20EXHL100040	10	4	Orange
12.20EXHL100050	10	5	Orange
-	10	6	Orange
-	10	0.5	Orange

#### Technical data

Extreema® XS roundsling				
HMPE EXS				
WLL	SF	Core ø mm	Weight kg 3m EWL	p/m extra kg
3t	7	9	0,8	0,25
5t	7	14	1,35	0,43
10t	7	23	2	0,65
15t	7	31	3,5	1,15
20t	7	37	4,6	1,50