

## Wire Rope Lifting Sling WLS-102

---

### Product information



**Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm<sup>2</sup>\***

(\* $\varnothing$  3mm -  $\varnothing$  7mm rope construction: 6x19M WSC 1960 N/mm<sup>2</sup>)

**Design:** One end soft eye. Other end thimble. Both mechanically spliced with alu. ferrule.

Load table at Technical Data -> Show table

Please specify the needed (working) length and eye diam/length with your request.

Other rope construction and/or end-terminations such as master links, shackles, hooks, etc.. possible on request. In that case, please check our website for more standard wire rope slings. You can also contact us to discuss the possible options or specify it with your request.

... [Read more](#)

---

## Wire Rope Lifting Sling WLS-102

### Technical data

Part code	Diameter mm	WLL ton
WLS10203	3	0.12
WLS10204	4	0.21
WLS10205	5	0.32
WLS10206	6	0.47
WLS10208	8	0.82
WLS10209	9	1.04
WLS10210	10	1.28
WLS10211	11	1.55
WLS10212	12	1.84
WLS10213	13	2.17
WLS10214	14	2.51
WLS10216	16	3.3
WLS10218	18	4.1
WLS10220	20	5.1
WLS10222	22	6.2
WLS10224	24	7.38
WLS10226	26	8.66
WLS10228	28	10.04
WLS10232	32	13.12
WLS10236	36	16.59
WLS10240	40	20.56
WLS10244	44	24.78
WLS10248	48	29.55
WLS10252	52	34.69