

## Wire Rope Lifting Sling WLS-113

---

### Product information



**Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm<sup>2</sup>\***

(\*ø 3mm - ø 7mm rope construction: 6x19M WSC 1960 N/mm<sup>2</sup>)

**Design:** Both ends mechanically spliced thimbles.

Load table at Technical Data -> [Show table](#)

Please specify the needed (working) length and eye diam/length with your request.

Other rope construction and/or end-terminations such as master links, shackles, hooks, etc.. possible on request. In that case, please check our website for more standard wire rope slings. You can also contact us to discuss the possible options or specify it with your request.

... [Read more](#)

---

## Wire Rope Lifting Sling WLS-113

### Technical data

Part code	Diameter mm	WLL ton
WLS11303	3	0.12
WLS11304	4	0.21
WLS11305	5	0.32
WLS11306	6	0.47
WLS11308	8	0.82
WLS11309	9	1.04
WLS11310	10	1.28
WLS11311	11	1.55
WLS11312	12	1.84
WLS11313	13	2.17
WLS11314	14	2.51
WLS11316	16	3.3
WLS11318	18	4.1
WLS11320	20	5.1
WLS11322	22	6.2
WLS11324	24	7.38
WLS11326	26	8.66
WLS11328	28	10.04
WLS11332	32	13.12
WLS11336	36	16.59
WLS11340	40	20.56
WLS11344	44	24.78
WLS11348	48	29.55
WLS11352	52	34.69