

Wire Rope Lifting Sling WLS-175

Product information



Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm²*

(* \varnothing 3mm - \varnothing 7mm rope construction: 6x19M WSC 1960 N/mm²)

Design: Master link in one end and eyehook with safety latch in other end, mechanical aluminium spliced.

Load table at Technical Data -> [Show table](#)

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as master links, shackles, hooks, etc.. possible on request. In that case, please check our website for more standard wire rope slings. You can also contact us to discuss the possible options or specify it with your request.

... [Read more](#)

Wire Rope Lifting Sling WLS-175

Technical data

Part code	Diameter mm	WLL ton
WLS17503	3	0.12
WLS17504	4	0.21
WLS17505	5	0.32
WLS17506	6	0.47
WLS17508	8	0.82
WLS17510	10	1.28
WLS17512	12	1.84
WLS17514	14	2.51
WLS17516	16	3.3
WLS17518	18	4.1
WLS17520	20	5.1
WLS17522	22	6.2
WLS17524	24	7.38
WLS17526	26	8.66
WLS17528	28	10.04
WLS17532	32	13.12
WLS17536	36	16.59
WLS17540	40	20.56
WLS17544	44	24.78
WLS17548	48	29.55
WLS17552	52	34.69