
MENNENS | Lifting Solutions Group
Axel Johnson International

Wire Rope Lifting Sling WLS-473

Product information



Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm2
Design: Master link in one end and thimble in other ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

... *Read more*

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Wire Rope Lifting Sling WLS-473

Technical data

Part code	Diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
WLS47303	3	0.25	0.25	0.18
WLS47304	4	0.44	0.44	0.31
WLS47305	5	0.68	0.68	0.49
WLS47306	6	0.98	0.98	0.7
WLS47308	8	1.72	1.72	1.23
WLS47309	9	2.18	2.18	1.56
WLS47310	10	2.69	2.69	1.92
WLS47311	11	3.25	3.25	2.32
WLS47312	12	3.85	3.85	2.75
WLS47313	13	4.55	4.55	3.25
WLS47314	14	5.28	5.28	3.77
WLS47316	16	6.9	6.9	4.93
WLS47318	18	8.71	8.71	6.22
WLS47320	20	10.75	10.75	7.68
WLS47322	22	13.03	13.03	9.31
WLS47324	24	15.5	15.5	11.07
WLS47326	26	18.19	18.19	13
WLS47328	28	21.08	21.08	15.06
WLS47332	32	27.56	27.56	19.69
WLS47336	36	34.84	34.84	24.89
WLS47340	40	43.17	43.17	30.84
WLS47344	44	52.04	52.04	37.17
WLS47348	48	62.06	62.06	44.33
WLS47352	52	75.85	75.85	52.04

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved