

## Wire Rope Lifting Sling WLS-473

---

### Product information



**Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm<sup>2</sup>**

**Design:** Master link in one end and thimble in other ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

... [Read more](#)

---

## Wire Rope Lifting Sling WLS-473

### Technical data

| Part code | Diameter<br>mm | WLL<br>ton | WLL 0-45°<br>t | WLL 45-60°<br>t |
|-----------|----------------|------------|----------------|-----------------|
| WLS47303  | 3              | 0.25       | 0.25           | 0.18            |
| WLS47304  | 4              | 0.44       | 0.44           | 0.31            |
| WLS47305  | 5              | 0.68       | 0.68           | 0.49            |
| WLS47306  | 6              | 0.98       | 0.98           | 0.7             |
| WLS47308  | 8              | 1.72       | 1.72           | 1.23            |
| WLS47309  | 9              | 2.18       | 2.18           | 1.56            |
| WLS47310  | 10             | 2.69       | 2.69           | 1.92            |
| WLS47311  | 11             | 3.25       | 3.25           | 2.32            |
| WLS47312  | 12             | 3.85       | 3.85           | 2.75            |
| WLS47313  | 13             | 4.55       | 4.55           | 3.25            |
| WLS47314  | 14             | 5.28       | 5.28           | 3.77            |
| WLS47316  | 16             | 6.9        | 6.9            | 4.93            |
| WLS47318  | 18             | 8.71       | 8.71           | 6.22            |
| WLS47320  | 20             | 10.75      | 10.75          | 7.68            |
| WLS47322  | 22             | 13.03      | 13.03          | 9.31            |
| WLS47324  | 24             | 15.5       | 15.5           | 11.07           |
| WLS47326  | 26             | 18.19      | 18.19          | 13              |
| WLS47328  | 28             | 21.08      | 21.08          | 15.06           |
| WLS47332  | 32             | 27.56      | 27.56          | 19.69           |
| WLS47336  | 36             | 34.84      | 34.84          | 24.89           |
| WLS47340  | 40             | 43.17      | 43.17          | 30.84           |
| WLS47344  | 44             | 52.04      | 52.04          | 37.17           |
| WLS47348  | 48             | 62.06      | 62.06          | 44.33           |
| WLS47352  | 52             | 75.85      | 75.85          | 52.04           |