

D Shackle with Safety Pin SS

Product information



Shackle manufactured from stainless steel EN10088 1.4404 (Marine Grade 316L). Excellent for lifting applications where a high level of corrosion resistance is required.

- Thick lugs on the shackle pins ensure that the product is both durable and dependable
- Special design of bolt ensures the nut is positioned correctly allowing sufficient room for the cotter pin
- Every shackle is proof load tested to 2 x WLL and certified at our manufacturing facility in the North East of England
- All shackles are manufactured in accordance with the Machine Directive 2006/42/EC
- Inspection certificate BS EN 10204 3.1 available on request
- High quality finish and excellent polish
- Manufactured using the latest technology in electrical upset forging

Material: Stainless steel 316L

Marking: CE-marked

Safety factor: 6:1

| Part code | WLL ton | Bolt mm | B mm | J mm | L mm | Weight kg |
|--------------|------------|------------|------|---------|---------|--------------|
| - | 0.35 | M6 | 6 | 13 | 25 | 0.048 |
| 11.39ED8M8 | 0.5 | M8 | 8 | 16 | 32 | 0.075 |
| - | 0.8 | M10 | 9.5 | 19 | 38 | 0.136 |
| 11.39ED11M12 | 1 | M12 | 11 | 22 | 44 | 0.212 |
| - | 1.25 | M12 | 12.7 | 26 | 52 | 0.331 |
| 11.39ED14M16 | 1.8 | M16 | 14.3 | 29 | 58 | 0.585 |
| - | 2.8 | M20 | 16 | 32 | 64 | 0.76 |
| - | 3.3 | M22 | 19 | 38 | 76 | 1.18 |
| 11.39ED22M24 | 4.5 | M24 | 22 | 44 | 88 | 1.75 |
| - | 5 | M27 | 25.4 | 50 | 100 | 2.6 |
| - | 7.5 | M33 | 28.6 | 57 | 114 | 3.1 |
| - | 10 | M36 | 31.8 | 64 | 128 | 4.35 |
| | 12 | M39 | 34.9 | 70 | 140 | 5.3 |

Blueprint

