MENNENS | Lifting Solutions Group
Axel Johnson International

DLB brake winch

Product information



Properties

- Zinc-plated housing (DL2500G has a ungalvanized drum).
- Fitted with automatic load pressure brakes.
- For extra safety, they are fitted with locking pawls.

Standard delivery

- Does not include cable.

Options

- Steel wire rope according DIN 3060 with safety hook.
- Sling belt according DIN 3060 with safety hook.

... *Read more*

Marking: According to standard, CE-mark
Standard: EN 12100, EN 13157
Warning: For lifting, select another wire rope diameter, taking tensile strength into consideration. Minimum load required for winch to operate properly.


Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

DLB brake winch

Blueprint



Technical data

Part code	Code	WLL ton	Model	Rope Ø mm	Lift/crank turn (mm)	Gear ratio	Max. reel capacity mm	Drum mm	Length handle mm	Hand force max. kg	Weight kg
501301590000250	8717365110580	0.159	DLB-350A	3	22.5	3.2 :1	25	26 x 52	178	10	3
501303600000250	8717365008979	0.36	DLB-800AG	4	36	4.4 :1	23	48 x 53	178	12	3
501305450000250	8717365008986	0.545	DLB-1200AG	5	39	5.4 :1	19.7	64 x 51	238	19	4
501306800000250	8717365008993	0.68	DLB-1500AG	6	40	5.4:1	15.1	64 x 62	305	18	5
501309050000250	8717365009006	0.905	DLB-2000AG	7	30	17.3 :1	8.9	64 x 54	238	8	7
501311350000250	8717365009013	1.135	DLB-2500G	8	23	12.0 :1	7.4	79 x 66	244	13	12

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved