Lifting Solutions Group
Axel Johnson International

Anchorage sling 3M™ Protecta®, Edge tested

Product information



Highly durable, high quality flat woven polyester anchorage sling for use in demanding applications. The field-tested polyester webbing sling is manufactured to particularly high standards and is certified to meet all the stringent requirements of EN795: 2012 / type B and has been tested for sharp edge (0.5 mm radius) use according VG11-074.

Webbing width: 25 mm

... *Read more*

Material: Polyester
Marking: According to standard, CE-mark, Supplier symbol, product id, art no, serial no, production year, standards, max. load.
Standard: EN 354, EN 566, EN 795B

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Anchorage sling 3M™ Protecta®, Edge tested

Technical data

Part code	Min. breaking force kN	Max. number of persons	Length m	Colour	Max load kg	Weight kg
821100801340	22	3	0.8	Grey	300	0.15
821100101340	22	3	1	Grey	300	0.2
821100151340	22	3	1.5	Grey	300	0.25
821100201340	22	3	2	Grey	300	0.3

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved