


Column Mounted Jib Crane ASSISTENT AS

Product information



Column mounted slewing jib crane for indoor or outdoor use (optional).

The ASSISTENT AS slewing jib crane is a versatile workplace crane with a capacity of up to 2.000 kg. The compact design means that the crane is perfectly suitable for small and narrow workspaces.

Jib design: Low-profile.

Advantages:

- High effective hook height
- Machine feeding with exact positioning
- Compact design
- Optional electrical slewing gear
- Outdoor use is possible

Contact our crane department for more information.

Marking: According to standard, CE-marked

Standard: EN 13001

Part code	WLL ton	Length m
AS0008-2000	0.08	2
AS0008-2500	0.08	2.5
AS0008-3000	0.08	3
AS0008-3500	0.08	3.5
AS0008-4000	0.08	4
AS0008-4500	0.08	4.5

AS0008-5000	0.08	5
AS0008-5500	0.08	5.5
AS0008-6000	0.08	6
AS0008-6500	0.08	6.5
AS0008-7000	0.08	7
AS0008-7500	0.08	7.5
AS0008-8000	0.08	8
AS0008-8500	0.08	8.5
AS0008-9000	0.08	9
AS0008-9500	0.08	9.5
AS0008-10000	0.08	10
AS0012-2000	0.125	2
AS0012-2500	0.125	2.5
AS0012-3000	0.125	3
AS0012-3500	0.125	3.5
AS0012-4000	0.125	4
AS0012-4500	0.125	4.5
AS0012-5000	0.125	5
AS0012-5500	0.125	5.5
AS0012-6000	0.125	6
AS0012-6500	0.125	6.5
AS0012-7000	0.125	7
AS0012-7500	0.125	7.5

AS0012-8000	0.125	8
AS0012-8500	0.125	8.5
AS0012-9000	0.125	9
AS0012-9500	0.125	9.5
AS0012-10000	0.125	10
AS0025-2000	0.25	2
AS0025-2500	0.25	2.5
AS0025-3000	0.25	3
AS0025-3500	0.25	3.5
AS0025-4000	0.25	4
AS0025-4500	0.25	4.5
AS0025-5000	0.25	5
AS0025-5500	0.25	5.5
AS0025-6000	0.25	6
AS0025-6500	0.25	6.5
AS0025-7000	0.25	7
AS0025-7500	0.25	7.5
AS0025-8000	0.25	8
AS0025-8500	0.25	8.5
AS0025-9000	0.25	9
AS0025-9500	0.25	9.5
AS0025-10000	0.25	10
AS0050-2000	0.5	2

AS0050-2500	0.5	2.5
AS0050-3000	0.5	3
AS0050-3500	0.5	3.5
AS0050-4000	0.5	4
AS0050-4500	0.5	4.5
AS0050-5000	0.5	5
AS0050-5500	0.5	5.5
AS0050-6000	0.5	6
AS0050-6500	0.5	6.5
AS0050-7000	0.5	7
AS0050-7500	0.5	7.5
AS0050-8000	0.5	8
AS0050-8500	0.5	8.5
AS0080-2000	0.8	2
AS0080-2500	0.8	2.5
AS0080-3000	0.8	3
AS0080-3500	0.8	3.5
AS0080-4000	0.8	4
AS0080-4500	0.8	4.5
AS0080-5000	0.8	5
AS0080-5500	0.8	5.5
AS0080-6000	0.8	6
AS0080-6500	0.8	6.5

AS0080-7000	0.8	7
AS0080-7500	0.8	7.5
AS0100-2000	1	2
AS0100-2500	1	2.5
AS0100-3000	1	3
AS0100-3500	1	3.5
AS0100-4000	1	4
AS0100-4500	1	4.5
AS0100-5000	1	5
AS0100-5500	1	5.5
AS0100-6000	1	6
AS0100-6500	1	6.5
AS0160-2000	1.6	2
AS0160-2500	1.6	2.5
AS0160-3000	1.6	3
AS0160-3500	1.6	3.5
AS0160-4000	1.6	4
AS0160-4500	1.6	4.5
AS0160-5000	1.6	5
AS0200-2000	2	2
AS0200-2500	2	2.5
AS0200-3000	2	3
AS0200-3500	2	3.5

Technical data

		Outreach [m]																
		2	2.5	3	3.5	4	4.5	5	5.5	6	6.5	7	7.5	8	8.5	9	9.5	10
Capacity [kg]	80	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
	125	■	■	■	■	■	■	■	■	■	■	■	■	■	□	□	□	□
	250	■	■	■	■	■	■	■	■	■	■	□	□	□	□	□	□	□
	500	■	■	■	■	■	■	□	□	□	□	□	□	□	□			
	800	■	■	■	■	□	□	□	□	□	□	□	□					
	1000	■	■	■	□	□	□	□	□	□	□							
	1600	□	□	□	□	□	□	□										
	2000	□	□	□	□	□	□											

□ Electrical slewing gear available (optional)