


Column Mounted Jib Crane PRIMUS PR

Product information



Column mounted slewing jib crane for indoor use. The PRIMUS slewing jib crane is a compact crane with infinite slewing range. It can be used in any workplace - also in small spaces and it is suitable to handle capacities up to 1.000 kg.

Jib design: Low-profile.

Features and advantages:

- Infinite slewing by 360° thanks to power supply by slip-ring assembly
- Especially easy slewing operation thanks to sophisticated ball bearing with pivot resistance regulator as standard feature
- Small stop clearance for maximum utilisation of effective outreach
- Compact design, perfectly suited for small rooms and installation on machines
- Large effective lifting height
- Column height and jib arm length can be adjusted to your conditions
- Easy to install thanks to dowelling on concrete floor (optional)

Contact our crane department for more information.

Marking: According to standard, CE-marked

Finish: Standard: coating according to Corrosion category C2 (Ral 1007), nominal thickness 80 µm.

Standard: EN 13001

Part code	WLL ton	Length m
PR0003-2000	0.03	2
PR0003-2500	0.03	2.5
PR0003-3000	0.03	3
PR0003-3500	0.03	3.5
PR0003-4000	0.03	4
PR0003-4500	0.03	4.5

PR0003-5000	0.03	5
PR0003-5500	0.03	5.5
PR0003-6000	0.03	6
PR0003-6500	0.03	6.5
PR0003-7000	0.03	7
PR0005-2000	0.05	2
PR0005-2500	0.05	2.5
PR0005-3000	0.05	3
PR0005-3500	0.05	3.5
PR0005-4000	0.05	4
PR0005-4500	0.05	4.5
PR0005-5000	0.05	5
PR0005-5500	0.05	5.5
PR0005-6000	0.05	6
PR0005-6500	0.05	6.5
PR0005-7000	0.05	7
PR0008-2000	0.08	2
PR0008-2500	0.08	2.5
PR0008-3000	0.08	3
PR0008-3500	0.08	3.5
PR0008-4000	0.08	4
PR0008-4500	0.08	4.5
PR0008-5000	0.08	5

PR0008-5500	0.08	5.5
PR0008-6000	0.08	6
PR0008-6500	0.08	6.5
PR0008-7000	0.08	7
PR0012-2000	0.125	2
PR0012-2500	0.125	2.5
PR0012-3000	0.125	3
PR0012-3500	0.125	3.5
PR0012-4000	0.125	4
PR0012-4500	0.125	4.5
PR0012-5000	0.125	5
PR0012-5500	0.125	5.5
PR0012-6000	0.125	6
PR0012-6500	0.125	6.5
PR0012-7000	0.125	7
PR0020-2000	0.2	2
PR0020-2500	0.2	2.5
PR0020-3000	0.2	3
PR0020-3500	0.2	3.5
PR0020-4000	0.2	4
PR0020-4500	0.2	4.5
PR0020-5000	0.2	5
PR0020-5500	0.2	5.5

PR0020-6000	0.2	6
PR0020-6500	0.2	6.5
PR0020-7000	0.2	7
PR0025-2000	0.25	2
PR0025-2500	0.25	2.5
PR0025-3000	0.25	3
PR0025-3500	0.25	3.5
PR0025-4000	0.25	4
PR0025-4500	0.25	4.5
PR0025-5000	0.25	5
PR0025-5500	0.25	5.5
PR0025-6000	0.25	6
PR0025-6500	0.25	6.5
PR0025-7000	0.25	7
PR0040-2000	0.4	2
PR0040-2500	0.4	2.5
PR0040-3000	0.4	3
PR0040-3500	0.4	3.5
PR0040-4000	0.4	4
PR0040-4500	0.4	4.5
PR0040-5000	0.4	5
PR0040-5500	0.4	5.5
PR0050-2000	0.5	2

PR0050-2500	0.5	2.5
PR0050-3000	0.5	3
PR0050-3500	0.5	3.5
PR0050-4000	0.5	4
PR0050-4500	0.5	4.5
PR0080-2000	0.8	2
PR0080-2500	0.8	2.5
PR0080-3000	0.8	3
PR0080-3500	0.8	3.5
PR0100-2000	1	2
PR0100-2500	1	2.5
PR0100-3000	1	3

Technical data

