

Wall Mounted Jib Crane GESELLE GN

Product information

The wall-mounted slewing jib crane GESELLE GN is the perfect help from the air.

It is the useful and efficient choice for workplaces where the floor needs to be free from obstacles and a column-mounted crane does not fit in for lack of space. It reduces utilisation of overhead cranes, accelerates work flow, and reduces costly downtime of staff and machines. This helpful crane can be used for feeding of machines, repair works, and in individual workplaces where capacities of up to 10,000 kg are required.

Due to its compact design, the crane features a maximum lifting height and is perfectly suitable for small and narrow operating rooms. With its optional electrical slewing gear, this slewing crane provides increased ease of use when operated in the higher capacity / outreach range. The wall-mounted slewing crane GN perfectly meets your requirements for indoor and outdoor use since its jib arm length can be adjusted individually.

Jib design: Low-profile.

Advantages:

- Compact design
- · Large effective lifting height
- Electrical slewing gear for comfortable/smooth slewing
- Outdoor use is possible
- Broad range of fastening options
- Suitable for explosion protection according to ATEX (option)

Contact our crane department for more information.

Marking: According to standard, CE-marked

Finish: Standard: coating according to Corrosion category C2 (Ral 1007), nominal thickness 80 µm.

Standard: EN 13001

Part code	WLL	Length
	ton	m

GN0012-6000 0.125 6

GN0012-6500	0.125	6.5
GN0012-7000	0.125	7
GN0012-7500	0.125	7.5
GN0012-8000	0.125	8
GN0012-8500	0.125	8.5
GN0012-9000	0.125	9
GN0012-9500	0.125	9.5
GN0012-10000	0.125	10
GN0012-10500	0.125	10.5
GN0012-2000	0.125	2
GN0012-11000	0.125	11
GN0012-11500	0.125	11.5
GN0012-12000	0.125	12
GN0012-2500	0.125	2.5
GN0012-3000	0.125	3
GN0012-3500	0.125	3.5
GN0012-4000	0.125	4
GN0012-4500	0.125	4.5
GN0012-5000	0.125	5
GN0025-2000	0.25	2
GN0025-2500	0.25	2.5
GN0025-3000	0.25	3
GN0025-3500	0.25	3.5

GN0025-4000	0.25	4
GN0025-4500	0.25	4.5
GN0025-5000	0.25	5
GN0025-5500	0.25	5.5
GN0025-6000	0.25	6
GN0025-6500	0.25	6.5
GN0025-7000	0.25	7
GN0025-7500	0.25	7.5
GN0025-8000	0.25	8
GN0025-8500	0.25	8.5
GN0025-9000	0.25	9
GN0025-9500	0.25	9.5
GN0025-10000	0.25	10
GN0025-10500	0.25	10.5
GN0025-11000	0.25	11
GN0025-11500	0.25	11.5
GN0025-12000	0.25	12
GN0050-2000	0.5	2
GN0050-2500	0.5	2.5
GN0050-3000	0.5	3
GN0050-3500	0.5	3.5
GN0050-4000	0.5	4
GN0050-4500	0.5	4.5

GN0050-5000	0.5	5
GN0050-5500	0.5	5.5
GN0050-6000	0.5	6
GN0050-6500	0.5	6.5
GN0050-7000	0.5	7
GN0050-7500	0.5	7.5
GN0050-8000	0.5	8
GN0050-8500	0.5	8.5
GN0050-9000	0.5	9
GN0050-9500	0.5	9.5
GN0050-10000	0.5	10
GN0050-10500	0.5	10.5
GN0050-11000	0.5	11
GN0050-11500	0.5	11.5
GN0050-12000	0.5	12
GN0100-2000	1	2
GN0100-3000	1	3
GN0100-3500	1	3.5
GN0100-4000	1	4
GN0100-4500	1	4.5
GN0100-5000	1	5
GN0100-5500	1	5.5
GN0100-6000	1	6

GN0100-6500	1	6.5
GN0100-7000	1	7
GN0100-7500	1	7.5
GN0100-8000	1	8
GN0100-8500	1	8.5
GN0100-9000	1	9
GN0100-9500	1	9.5
GN0100-10000	1	10
GN0100-10500	1	10.5
GN0100-11000	1	11
GN0100-11500	1	11.5
GN0100-12000	1	12
GN0160-9000	1.6	9
GN0160-9500	1.6	9.5
GN0160-10000	1.6	10
GN0160-10500	1.6	10.5
GN0160-11000	1.6	11
GN0160-11500	1.6	11.5
GN0160-12000	1.6	12
GN0160-2000	1.6	2
GN0160-2500	1.6	2.5
GN0160-3000	1.6	3
GN0200-2000	2	2

GN0200-2500	2	2.5
GN0200-3000	2	3
GN0200-3500	2	3.5
GN0200-4000	2	4
GN0200-4500	2	4.5
GN0200-5000	2	5
GN0200-5500	2	5.5
GN0200-6000	2	6
GN0200-6500	2	6.5
GN0200-7000	2	7
GN0200-7500	2	7.5
GN0200-8000	2	8
GN0200-8500	2	8.5
GN0200-9000	2	9
GN0200-9500	2	9.5
GN0200-10000	2	10
GN0200-10500	2	10.5
GN0200-11000	2	11
GN0200-11500	2	11.5
GN0200-12000	2	12
GN0250-2000	2.5	2
GN0250-2500	2.5	2.5
GN0250-3000	2.5	3

GN0250-3500	2.5	3.5
GN0250-4000	2.5	4
GN0250-4500	2.5	4.5
GN0250-5000	2.5	5
GN0250-5500	2.5	5.5
GN0250-6000	2.5	6
GN0250-6500	2.5	6.5
GN0250-7000	2.5	7
GN0250-7500	2.5	7.5
GN0250-8000	2.5	8
GN0250-8500	2.5	8.5
GN0250-9000	2.5	9
GN0250-9500	2.5	9.5
GN0250-10000	2.5	10
GN0250-10500	2.5	10.5
GN0250-11000	2.5	11
GN0320-2000	3.2	2
GN0320-2500	3.2	2.5
GN0320-3000	3.2	3
GN0320-3500	3.2	3.5
GN0320-4000	3.2	4
GN0320-4500	3.2	4.5
GN0320-5000	3.2	5

GN0320-5500	3.2	5.5
GN0320-6000	3.2	6
GN0320-6500	3.2	6.5
GN0320-7000	3.2	7
GN0320-7500	3.2	7.5
GN0320-8000	3.2	8
GN0320-8500	3.2	8.5
GN0320-9000	3.2	9
GN0320-9500	3.2	9.5
GN0400-2000	4	2
GN0400-2500	4	2.5
GN0400-3000	4	3
GN0400-3500	4	3.5
GN0400-4000	4	4
GN0400-4500	4	4.5
GN0400-5000	4	5
GN0400-5500	4	5.5
GN0400-6000	4	6
GN0400-6500	4	6.5
GN0400-7000	4	7
GN0400-7500	4	7.5
GN0400-8000	4	8
GN0400-8500	4	8.5

GN0400-9500	4	9.5
GN0400-10000	4	10
GN0400-10500	4	10.5
GN0400-11000	4	11
GN0500-2000	5	2
GN0500-2500	5	2.5
GN0500-3000	5	3
GN0500-3500	5	3.5
GN0500-4000	5	4
GN0500-4500	5	4.5
GN0500-5000	5	5
GN0500-5500	5	5.5
GN0500-6000	5	6
GN0500-6500	5	6.5
GN0500-7000	5	7
GN0500-7500	5	7.5
GN0630-2000	6.3	2
GN0630-2500	6.3	2.5
GN0630-3000	6.3	3
GN0630-3500	6.3	3.5
GN0630-4000	6.3	4
GN0630-4500	6.3	4.5
GN0630-5000	6.3	5

GN0630-5500	6.3	5.5
GN0630-6000	6.3	6
GN0630-6500	6.3	6.5
GN0800-2000	8	2
GN0800-2500	8	2.5
GN0800-3000	8	3
GN0800-3500	8	3.5
GN0800-4000	8	4
GN0800-4500	8	4.5
GN1000-2000	10	2
GN1000-2500	10	2.5
GN1000-3000	10	3
GN1000-3500	10	3.5
GN1000-4000	10	4

Technical data

											Out	reacl	ր [m]									
		2	2.5	3	3.5	4	4.5	5	5.5	6	6.5	7	7.5	8	8.5	9	9.5	10	10.5	11	11.5	12
	125	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	250	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	٠	•	•
	500	٠	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	1000	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
(g)	1600	٠	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	٠	•	•
Capacity [kg]	2000	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
apac	2500	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
0-	3200	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•					
	4000	•	•	•	•	•	•	•	•	•	•	•	•	•	•							
	5000	•	•	•	•	•	•	•	•	•	•	•	•									
_	6300	•	•	•	•	•	•	•	•	•												
	8000	•	•	•	•	•	•															
	10000	•	•	•	•	•																