MENNENS | Lifting Solutions Group
Axel Johnson International

Mobile Jib Crane MOBILUS MOB-AS

Product information



The MOB-AS is a mobile column slewing crane with a rotation range of 270°. Thanks to its compact design, this slewing crane is extremely suitable for small and narrow workshops or workspaces. The crane offers various options for relocation, such as a mobile base manual movable or with forklift connector bar, fork lift truck pockets, or lifting eyes for movement with an overhead crane (all optional).

Slewing Crane Custom Configuration:

The mobile crane MOB-AS can be perfectly configured to your specific requirements. The column height and the length of the lifting arm can be adjusted to size. Thanks to the integrated counterweight in the crane base, the MOB-AS is completely independent and does not require anchoring to the foundation or drilling into the concrete floor. Because the crane is movable, it is standard equipped with a locking device for securing the crane arm, which is mandatory for movable slewing cranes.

Standard features:

- Capacity range: 125 - 500 kg
- Outreach: 2000 - 6000 mm
- slewing range: 270°
- Crane height: 2120 - 5250 mm
- Height under crane arm: 1800 - 5000 mm

Crane arm Design: The crane arm is designed with an I-profile and under bracing, ensuring a robust and reliable construction.

Advantages:

- No attachment required;

... *Read more*

Marking: According to standard, CE-mark
Standard: EN 13001
Note: It's not allowed to move the crane under load.

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Mobile Jib Crane MOBILUS MOB-AS

Technical data

Part code	WLL ton	Length m
6021MOBAS00122000	0.125	2
6021MOBAS00122500	0.125	2.5
6021MOBAS00123000	0.125	3
6021MOBAS00123500	0.125	3.5
6021MOBAS00124000	0.125	4
6021MOBAS00124500	0.125	4.5
6021MOBAS00125000	0.125	5
6021MOBAS00125500	0.125	5.5
6021MOBAS00126000	0.125	6
6021MOBAS00252000	0.25	2
6021MOBAS00252500	0.25	2.5
6021MOBAS00253000	0.25	3
6021MOBAS00253500	0.25	3.5
6021MOBAS00254000	0.25	4
6021MOBAS00254500	0.25	4.5
6021MOBAS00255000	0.25	5
6021MOBAS00322000	0.32	2
6021MOBAS00322500	0.32	2.5
6021MOBAS00323000	0.32	3
6021MOBAS00323500	0.32	3.5
6021MOBAS00324000	0.32	4
6021MOBAS00324500	0.32	4.5
6021MOBAS00502000	0.5	2
6021MOBAS00502500	0.5	2.5
6021MOBAS00503000	0.5	3

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved