

## Sliding Beam Anchor 3M DBI Sala

### Product information



The 3M™ DBI-SALA® Sliding Beam Anchor. This system provides a high-quality anchorage point for use on steel beams – I-profiles that follow you as you work. Once you have secured the anchor to the beam using the integrated adjustment knobs, all you need to do is connect the fall arrest block or fall arrest line to the swivel D-ring to get to work.

#### 3 Acceptable orientations for Installation:

- top flange
- bottom flange
- side flange (if the profile is installed in this way).

#### Applications:

Recommended for use in construction, general industry, mining, oil and gas, transport, utilities and wind energy sectors.

#### Advantages:

- Compatible with various fall protection systems
- Compact, lightweight design
- Easy to assemble and disassemble.
- Quick to adjust to the correct size.
- Ideal for use with personal fall protection systems with self-retracting lines - fall arrest blocks
- Hands-free Mobility 360-degree swiveling D-ring optimizes mobility on the beam
- Portable and reusable
- Corrosion-resistant construction for durability
- Classified for ATEX zone 2

**Material:** Aluminum - Stainless steel

**Marking:** According to standard

**Standard:** EN 795-B

<b>Part code</b>	<b>Size</b>	<b>Max. number of persons</b>	<b>Length m</b>	<b>Max user weight kg</b>	<b>Max flange thickness mm</b>	<b>Flange width mm</b>	<b>Weight kg</b>
2104711	Medium	1	0.52	140	320	90 - 355	1.5
2104716	Large	1	0.98	140	320	305 - 762	3.3