

## GL100 Cablegrip closed with thimble

### Product information

**General:** Tool for mounting of wire ropes.

**Design:** Closed with one thimble.

Also available in special editions in larger sizes and stainless material.

**Material:** Galvanized steelwire 1960N/mm<sup>2</sup>



| Part code         | Rope Ø range<br>mm | Length<br>mm | Max. pullingforce<br>kN | Thimble Ø<br>mm |
|-------------------|--------------------|--------------|-------------------------|-----------------|
| 10.15KBZ106/1000  | 6-8                | 1,000        | 3.3                     | 13              |
| 10.15KBZ108/1000  | 8-10               | 1,000        | 4.6                     | 14              |
| 10.15KBZ110/1250  | 8-15               | 1,250        | 6.2                     | 18              |
| 10.15KBZ115/1250  | 15-20              | 1,250        | 12.8                    | 18              |
| 10.15KBZ120/1250  | 20-30              | 1,250        | 16                      | 18              |
| 10.15KBZ130/1250  | 30-40              | 1,250        | 19.2                    | 20              |
| 10.15KBZ140/1250  | 40-50              | 1,250        | 22.4                    | 20              |
| 10.15KBZ150/1250  | 50-60              | 1,250        | 37.4                    | 24              |
| 10.15KBZ160/1250  | 60-70              | 1,250        | 49.9                    | 28              |
| 10.15KBZ170/1250  | 70-80              | 1,250        | 49.9                    | 28              |
| 10.15KBZ180/1250  | 80-90              | 1,250        | 56.2                    | 28              |
| 10.15KBZ190/1250  | 90-100             | 1,250        | 62.4                    | 28              |
| 10.15KBZ1100/1250 | 100-115            | 1,250        | 62.4                    | 28              |
| 10.15KBZ1115/1500 | 115-130            | 1,500        | 74.8                    | 45              |
| 10.15KBZ1130/1500 | 130-150            | 1,500        | 74.8                    | 45              |
| 10.15KBZ1150/1500 | 150-180            | 1,500        | 87.3                    | 45              |
| 10.15KBZ1180/1500 | 180-210            | 2,000        | 99.8                    | 60              |
| 10.15KBZ1210/1500 | 210-240            | 1,500        | 99.8                    | 60              |

## Technical data