

## Rope Socket Demag

### Product information



1) Wire rope Diameter in acc. to DIN EN 12385 ( former DIN 3051 – 3071).

2) For socketing only use the following materials: DF-VM Art. Nr. 01-7016010, TEGO VG3 Art. Nr. 01-7016028, or Wirelock. Please obtain the socketing guidelines 20612044 (720 IS 817) and DIN EN 13411-4. Socketing Materials have the approval from the Germanischen Lloyd. Weight for socketing material are listed for 1 socket.

4) Delivery time on request.

Don't use ropes with bigger diameter as listed in the chart even NOT when the dimension "d" in the chart allows the use of bigger rope diameters.

**Material:** Permanent rope connectors make it possible to change load handling attachments quickly by simply detaching and connecting the grab ropes to the closing ropes on the hoist unit.

**Marking:** Producer, Size, Batch No.

Part code	Rope Ø range mm	Size	A mm	e mm mm	f mm mm	g mm mm	rmm mm	Weight kg
9170011	10	1.5	69	48	12	1	195	0.3
9170002	11-12	1.5	78.5	56	15.5	2	195	0.42
9170003	13-14	1.5	90.5	64	17.5	3	220	0.67
9170004	15-16	1.5	102.5	70	19.5	4	220	0.95
9170005	18	1.5	114	84	21	5	245	1.3
9170006	19-20	2	129	84	23	6	310	1.6
9170007	22-24	2	140	100	26	7	310	2.4
9170008	26	2	158	100	28	8	350	2.6
9170009	28	2	171	120	31	9	350	3.6
9171000	32	2	190	120	32	10	445	4.4
9171001	35	2	203	142	36	11	445	6
9171002	36	2.5	225	142	39	12	495	7.5
9171003	40	2.5	242	166	43	13	555	9
9171004	44	2.5	265	166	47	14	595	11.5
9171005	48	2.5	286	166	49	15	595	12.5
9171006	64	2.5	400	250	75	17	950	30

# Blueprint

