

Kiswire Steel Wire Rope 35x7 | rotation resistant

Product information



Rotation resistant galvanized multistrand lifting cable from the renowned steel wire rope manufacturer Kiswire. High- and consistent quality guaranteed!


Applications: Suitable for, for example, tower cranes, mobile cranes, electric hoists, and other applications where a non-rotating construction is required.

Laying method: RHOL Right-Hand-Ordinary-Lay, sZ (standard), Lang's Lay (zZ) on request

ISO 4309 Cable Category No.: all diameters RCN.23-2

Rope construction: 35x7

RCN: 23-2



Part code	Rope diameter mm	Tensile strength N/mm ²	Finish	Rope lay	Min. breaking force kN	Steel area mm ²	Lubrication	Weight kg/100m
102100804270282	8	1,960	Galvanized	sZ	45.2	-	A-2	28.8
102100904270282	9	1,960	Galvanized	sZ	57.2	-	A-2	36.8
102101004270282	10	1,960	Galvanized	sZ	70.6	-	A-2	45.4
102101004270282	11	1,960	Galvanized	sZ	85.4	-	A-2	54.9
102101004270282	12	1,960	Galvanized	sZ	102	-	A-2	65.4
102101304270282	13	1,960	Galvanized	sZ	119	-	A-2	76.7
102101404270282	14	1,960	Galvanized	sZ	138	-	A-2	89
102101604270282	16	1,960	Galvanized	sZ	181	-	A-2	116.2