

## Spreader Multi Position

---

### Product information



### CERTEX

**General:** Low profile lifting beam for minimum head room. Central eye is adjustable to be able to position the eye above the centre of gravity of the load. With several lifting points for max. flexibility. The table only shows a few examples of available sizes and provide an indications of dimensions, loads and weights. Other lengths and working loads can be manufactured to suit customer requirements. All beams are supplied complete with shackles according to the table. The beams can be provided with other accessories such as hooks, wire rope slings, chain slings or textile slings. Please also refer to our description in the introduction to this section on lifting beams.

**Design:** Lightweight welded beam construction providing good torsional stiffness.

**Proof:** 1,5 x WLL.

... [Read more](#)

---

**Material:** Beam and plate of high-strength structural steel.

**Marking:** Working load limit and CE marking.

**Finish:** Yellow painted.

## Spreader Multi Position

### Technical data

| Part code          | WLL ton | Length m | WLL t   |
|--------------------|---------|----------|---------|
| 13.356610MU005xxx  | 0.5     | 1-6      | -       |
| 13.356610MU010xxx  | 1       | 1-6      | -       |
| 13.356610MU020xxx  | 2       | 1-6      | -       |
| 13.356610MU030xxx  | 3       | 1-6      | -       |
| 13.356610MU040xxx  | 4       | 1-6      | -       |
| 13.356610MU050xxx  | 5       | 1-6      | -       |
| 13.356610MU060xxx  | 6       | 1-6      | -       |
| 13.356610MU080xxx  | 8       | 1-6      | -       |
| 13.356610MU100xxx  | 10      | 1-6      | -       |
| 13.356610MU120xxx  | 12      | 1-6      | -       |
| 13.356610MU150xxx  | 15      | 1-6      | -       |
| 13.356610MU200xxx  | 20      | 1-6      | -       |
| 13.356610MUyyyyxxx | -       | 1-6      | >20 Ton |