

## Spreader Type 6650 Adjustable

### Product information



### CERTEX

**General:** The spreaders have a high point of oscillation which results in good balance. The table only shows a few examples of available sizes and provide an indication of dimensions, loads and weights. Other lengths and working loads can be manufactured to suit a customers requirements. All spreaders are supplied complete with 2-leg sling and shackles according to the table. The beams can be provided with other accessories such as hooks, wire rope slings, chain slings or textile slings. Please also refer to our description in the introduction to this section on lifting beams.

**Design:** Lightweight welded pipe beam construction providing good torsional stiffness.

**Proof:** 1,5 x WLL.

... [Read more](#)

**Material:** Hollow beam and plate manufactured with high-strength structural steel.

**Marking:** Working load limit and CE marking.

**Finish:** Yellow painted.

## Spreader Type 6650 Adjustable

### Technical data

Part code	WLL ton	Length m	WLL t
13.406650TL020xxx	2	1-6	-
13.406650TL040xxx	4	1-6	-
13.406650TL060xxx	6	1-6	-
13.406650TL100xxx	10	1-6	-
13.406650TL150xxx	15	1-6	-
13.406650TL200xxx	20	1-6	-
13.406650TL250xxx	25	1-6	-
13.406650TLyyyyxxx	-	1-6	>25 Ton