

## **Coil Hook Type CKBM**

## **Product information**



## Counterbalanced

General: For small or medium-sized loads and moderate coil widths. See the introductory text above in the section on C-hooks.

**Design:** Hollow beam that is lighter in weight than equivalent steel plate. The counterbalance ensures that the fork is always in a horizontal position, regardless of whether the hook is empty or loaded.

Proof: 1,5 x WLL.

Material: Hollow-beam of high-strength structural steel.

Marking: Type, working load limit, maximum coil width and CE marking.

Finish: Yellow painted.

Note: We recommend the use a of 2-leg chain sling, headroom permitting as an increase in dimension L provides better balance.

Safety factor: 1,5 x WLL.

| Part code      | WLL<br>ton | Max coil width<br>mm | B mm | C mm | E<br>mm | G<br>mm | H<br>mm | L<br>mm | S<br>mm | Weight<br>kg |
|----------------|------------|----------------------|------|------|---------|---------|---------|---------|---------|--------------|
| 16.80CKBM15-38 | 1.5        | 380                  | 50   | 100  | 300     | 100     | 500     | 300     | 110     | 25           |
| 16.80CKBM20-50 | 2          | 500                  | 50   | 100  | 375     | 60      | 500     | 310     | 120     | 80           |
| 16.80CKBM35-85 | 3.5        | 850                  | 75   | 150  | 600     | 100     | 500     | 420     | 150     | 130          |
| 16.80CKBM75-85 | 7.5        | 850                  | 90   | 200  | 750     | 100     | 550     | 500     | 200     | 240          |

## Blueprint

