

Wall Jib Crane Overbraced, Hollow Section 180° PMTC

Product information



The jib crane PMTC is reserved for an indoor use and built with a hollow section, PMTC allows 180° rotation. This jib crane cannot be motorized.

Intended to be equipped with a manual or electric hoist, this model has a great versatility with his trolley hoist mounted on plastic rollers.

These jib cranes are delivered with standard mounting brackets. Our mounting kits KITFIX guarantee safe anchorages for specific supports.

A full range of accessories is available.

Options

- Lockable main switch
- Standpipe
- Rotation slowing device (adaptable without welding or mechanical intervention)
- Rotation stops to weld onto the assembly
- Single- or multipositions rotation lock
- Electric or manual hoist

Part code	WLL ton	Length m	Cap. kg
6025PMTC015	0.05	2	50
-	0.05	2.5	50
-	0.05	3	50
-	0.05	3.5	50
-	0.05	4	50

-		0.05	4.5	50
-		0.05	5	50
-		0.05	5.5	50
-		0.05	6	50
-		0.05	6.5	50
-		0.05	7	50
-		0.05	7.5	50
-		0.05	8	50
6025PMTC025		0.08	2	80
-		0.08	2.5	80
6025PMTC050		0.15	2	150
-		0.15	2.5	150
-		0.15	3	150
-		0.15	3.5	150
-		0.15	4	150
-		0.15	4.5	150
-		0.15	5	150
-		0.15	5.5	150
-		0.15	6	150
-		0.15	6.5	150
-		0.15	7	150
-		0.15	7.5	150
-		0.15	8	150

6025PMTC100		0.25	2	250
-		0.25	2.5	250
-		0.25	3	250
-		0.25	3.5	250
-		0.25	4	250
-		0.25	4.5	250
-		0.25	5	250
-		0.25	5.5	250
-		0.25	6	250
-		0.25	6.5	250
-		0.25	7	250
-		0.25	7.5	250
-		0.25	8	250
6025PMTC160		0.5	2	500
-		0.5	2.5	500
-		0.5	3	500
-		0.5	3.5	500
-		0.5	4	500
-		0.5	4.5	500
-		0.5	5	500
-		0.5	5.5	500
-		0.5	6	500
-		0.5	6.5	500

-		0.5	7	500
-		0.5	7.5	500
-		0.5	8	500
6025PMTC200		1	2	1,000
-		1	2.5	1,000
-		1	3	1,000
-		1	3.5	1,000
-		1	4	1,000
-		1	4.5	1,000
-		1	5	1,000
-		1	5.5	1,000
-		1	6	1,000
-		1	6.5	1,000
-		1	7	1,000
-		1	7.5	1,000
-		-	3	80
-		-	3.5	80
-		-	4	80
-		-	4.5	80
-		-	5	80
-		-	5.5	80
-		-	6	80
-		-	6.5	80

7 80

7.5 80

8 80