

Wall Jib Crane Overbraced 180° PMT

Product information



General

Appropriate for an indoor or outdoor use, the beam of the PMT is built on an I beam profile. Its light weight gives it great flexibility for rotations of 180°. The structure of this jib crane is suitable for the optional installation of a hoist motor direction. The PMT are delivered with standard mounting brackets and our mounting kits KITFIX (optional) ensure safe anchorages for specific supports.

A full range of accessories is available.

Options

- Hoist power supply cable + lockable main switch
- Standpipe
- Rotation slowing device (adaptable without welding or mechanical intervention)
- Hot dip galvanizing (contact us)
- Rotation stops to weld onto the assembly
- Single- or multi-position rotation lock
- Outdoor use
- Electric or manual hoist

| Part code | WLL ton | Length m | Cap. kg |
|--------------|------------|-------------|------------|
| 6025PMT015 | 0.15 | 2 | 150 |
| PMT0015-2500 | 0.15 | 2.5 | 150 |
| PMT0015-3000 | 0.15 | 3 | 150 |
| PMT0015-3500 | 0.15 | 3.5 | 150 |
| PMT0015-4000 | 0.15 | 4 | 150 |
| PMT0015-4500 | 0.15 | 4.5 | 150 |

| | | | |
|--------------|------|-----|-----|
| PMT0015-5000 | 0.15 | 5 | 150 |
| PMT0015-5500 | 0.15 | 5.5 | 150 |
| PMT0015-6000 | 0.15 | 6 | 150 |
| PMT0015-6500 | 0.15 | 6.5 | 150 |
| PMT0015-7000 | 0.15 | 7 | 150 |
| PMT0015-7500 | 0.15 | 7.5 | 150 |
| 6025PMT025 | 0.25 | 2 | 250 |
| PMT0025-2500 | 0.25 | 2.5 | 250 |
| PMT0025-3000 | 0.25 | 3 | 250 |
| PMT0025-3500 | 0.25 | 3.5 | 250 |
| PMT0025-4000 | 0.25 | 4 | 250 |
| PMT0025-4500 | 0.25 | 4.5 | 250 |
| PMT0025-5000 | 0.25 | 5 | 250 |
| PMT0025-5500 | 0.25 | 5.5 | 250 |
| PMT0025-6000 | 0.25 | 6 | 250 |
| PMT0025-6500 | 0.25 | 6.5 | 250 |
| PMT0025-7000 | 0.25 | 7 | 250 |
| PMT0025-7500 | 0.25 | 7.5 | 250 |
| 6025PMT050 | 0.5 | 2 | 500 |
| PMT0050-2500 | 0.5 | 2.5 | 500 |
| PMT0050-3000 | 0.5 | 3 | 500 |
| PMT0050-3500 | 0.5 | 3.5 | 500 |
| PMT0050-4000 | 0.5 | 4 | 500 |

| | | | |
|--------------|-----|-----|-------|
| PMT0050-4500 | 0.5 | 4.5 | 500 |
| PMT0050-5000 | 0.5 | 5 | 500 |
| PMT0050-5500 | 0.5 | 5.5 | 500 |
| PMT0050-6000 | 0.5 | 6 | 500 |
| PMT0050-6500 | 0.5 | 6.5 | 500 |
| PMT0050-7000 | 0.5 | 7 | 500 |
| PMT0050-7500 | 0.5 | 7.5 | 500 |
| 6025PMT100 | 1 | 2 | 1,000 |
| PMT0100-2500 | 1 | 2.5 | 1,000 |
| PMT0100-3000 | 1 | 3 | 1,000 |
| PMT0100-3500 | 1 | 3.5 | 1,000 |
| PMT0100-4000 | 1 | 4 | 1,000 |
| PMT0100-4500 | 1 | 4.5 | 1,000 |
| PMT0100-5000 | 1 | 5 | 1,000 |
| PMT0100-5500 | 1 | 5.5 | 1,000 |
| PMT0100-6000 | 1 | 6 | 1,000 |
| PMT0100-6500 | 1 | 6.5 | 1,000 |
| PMT0100-7000 | 1 | 7 | 1,000 |
| PMT0100-7500 | 1 | 7.5 | 1,000 |
| 6025PMT160 | 1.6 | 2 | 1,600 |
| PMT0160-2500 | 1.6 | 2.5 | 1,600 |
| PMT0160-3000 | 1.6 | 3 | 1,600 |
| PMT0160-3500 | 1.6 | 3.5 | 1,600 |

| | | | |
|--------------|-----|-----|-------|
| PMT0160-4000 | 1.6 | 4 | 1,600 |
| PMT0160-4500 | 1.6 | 4.5 | 1,600 |
| PMT0160-5000 | 1.6 | 5 | 1,600 |
| PMT0160-5500 | 1.6 | 5.5 | 1,600 |
| PMT0160-6000 | 1.6 | 6 | 1,600 |
| 6025PMT200 | 2 | 2 | 2,000 |
| PMT0200-2500 | 2 | 2.5 | 2,000 |
| PMT0200-3000 | 2 | 3 | 2,000 |
| PMT0200-3500 | 2 | 3.5 | 2,000 |
| PMT0200-4000 | 2 | 4 | 2,000 |
| PMT0200-4500 | 2 | 4.5 | 2,000 |
| PMT0200-5000 | 2 | 5 | 2,000 |
| PMT0200-5500 | 2 | 5.5 | 2,000 |
| PMT0200-6000 | 2 | 6 | 2,000 |