

## Wall Jib Crane Articulated PMA

### Product information



This articulated jib crane has a very reduced headroom. Its first arm can rotate 180° degrees and the second 300°. The articulated structure facilitates the movement of loads in a cluttered environment. This model is restricted to only manual rotations.

The PMA are delivered with standard mounting brackets and our mounting kits KITFIX (optional) ensure safe anchorages for specific supports.

A full range of accessories is available.

### Options

- Hoist power supply cable + lockable main switch
- Standpipe
- Rotation slowing device (adaptable without welding or mechanical intervention)
- Option of a slowing device on each arm
- Hot dip galvanizing (contact us)
- Rotation stops to weld onto the assembly
- Single- or multipositions rotation lock (arm 1 only)
- Electric or manual hoist
- Outdoor use

Also available as a column

Part code	WLL ton	Length m	Cap. kg
6025PMA013	0.125	2	125
PMA0012-2500	0.125	2.5	125
PMA0012-3000	0.125	3	125
PMA0012-3500	0.125	3.5	125
PMA0012-4000	0.125	4	125
PMA0012-4500	0.125	4.5	125
PMA0012-5000	0.125	5	125
6025PMA025	0.25	2	250
PMA0025-2500	0.25	2.5	250
PMA0025-3000	0.25	3	250
PMA0025-3500	0.25	3.5	250
PMA0025-4000	0.25	4	250
PMA0025-4500	0.25	4.5	250
PMA0025-5000	0.25	5	250