

Pillar jib crane, overbraced, 270°: PFT



Product information

Appropriate for an indoor or outdoor use, the beam of the PFT is built on an I beam profile. Its light weight gives it great flexibility for rotations of 180 °. The structure of this jib crane is suitable for the optional installation of a hoist motor direction.

A full range of accessories is available.

Floor fixing is effected by chemical anchors or anchor rods with foundation.

Options

- Installation template + anchor rods (or base plate for chemical anchors, keeping its limitations in mind).
- Hoist power supply cable.
- Lockable main switch.
- Rotation slowing device (adaptable without welding or mechanical intervention).
- Hot dip galvanizing (contact us).
- Rotation stops to weld onto the assembly, or adjustable.
- Single or multipositions rotation lock.
- Electric or manual hoist.
- Outdoor use.

Cap. kg	Span m 2,0	Span m 2,5	Span m 3,0	Span m 3,5	Span m 4,0	Span m 4,5	Span m 5,0	Span m 5,5	Span m 6,0	Span m 6,5	Span m 7,0
150	•	•	•	•	•	•	•	•	•	•	•
250	•	•	•	•	•	•	•	•	•	•	•
500	•	•	•	•	•	•	•	•	•	•	•
1,000	•	•	•	•	•	•	•	•	•	•	•
1,600	•	•	•	•	•	•	•	-	-	-	-
2,000	•	•	•	•	•	•	•	-	-	-	-