

Pillar jib crane, underbraced, 360°: PRT

Product information

Appropriate for an indoor or outdoor use, the beam of the PRT is built on an I beam profile designed for an intensive use. The total rotation is on 360 ° and can be assisted by an engine (optional). The optional installation of a hoist motor direction is possible.

Floor fixing is effected by chemical anchors or anchor rods with foundation.

This model has a wide range of mechanical and electrical options.

Options

- Installation template + anchor rods (or base plate for chemical anchors, keeping its limitations in mind).
- Motorization on main roller (indoor use).
- Top-mounted motorization (outdoor use).
- Hoist power supply cable.
- · Lockable main switch.
- 4-ring electrical collector, for unlimited rotation.
- Hot dip galvanizing (contact us).
- Rotation stops to weld onto the assembly.
- Single- or multipositions rotation lock.
- Outdoor use.
- · Electric or manual hoist.

Part Code	WLL ton	Cap. kg	Span m 2,0	Span m 2,5	Span m 3,0	Span m 3,5	Span m 4,0	Span m 4,5	Span m 5,0	Span m 5,5	Span m 6,0		Span m 7,0		Span m 8,0		Span m 9,0	Span m 9,5	Span m 10,0	Span m 10,5	Span m 11,0	Span m 11,5	Span m 12,0
6025PRT0015	0.15	150	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
6025PRT0025	0.25	250	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
6025PRT0050	0.5	500	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
6025PRT0100	1	1,000	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
6025PRT0160	1.6	1,600	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
6025PRT0200	2	2,000	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
6025PRT0250	2.5	2,500	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
6025PRT0320	3.2	3,200	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	-	-
6025PRT0400	4	4,000	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	-	-	-	-
6025PRT0500	5	5,000	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	-	-	-	-	-	-
6025PRT0630	6.3	6,300	•	•	•	•	•	•	•	•	•	•	•	-	-	-	-	-	-	-	-	-	-
6025PRT0800	8	8,000	•	•	•	•	•	•	•	•	•	-	-	-	-	-	-	-	-	-	-	-	-
6025PRT1000	10	10,000	•	•	•	•	•	•	•	•	-	-	-	-	-	-	-	-	-	-	-	-	-