

Pillar Jib Crane Articulated PFA

Product information



Appropriate for an indoor or outdoor use, this articulated jib crane has a very reduced headroom. The first arm can rotate 270° and the second 300°. The articulated structure facilitates the movement of loads in a cluttered environment. This model is restricted to only manual rotations. Floor fixing is effected by chemical anchors or anchor rods with foundation.

A full range of accessories is available.

Options

- Installation template + anchor rods (or base plate for chemical anchors, keeping its limitations in mind)
- Hoist power supply cable
- Lockable main switch
- Rotation slowing device (adaptable without welding or mechanical intervention)
- Option of a slowing device on each arm
- Hot dip galvanizing (contact us)
- Rotation stops to weld onto the assembly, or adjustable, on 1 arm
- Single- or multipositions rotation lock (arm 1 only)
- Outdoor use
- Electric or manual hoist

[... Read more](#)

Pillar Jib Crane Articulated PFA

Technical data

Part code	WLL ton	Length m	Cap. kg
6025PFA0125	0.125	2	125
PFA0012-2500	0.125	2.5	125
PFA0012-3000	0.125	3	125
PFA0012-3500	0.125	3.5	125
PFA0012-4000	0.125	4	125
PFA0012-4500	0.125	4.5	125
PFA0012-5000	0.125	5	125
6025PFA0250	0.25	2	250
PFA0025-2500	0.25	2.5	250
PFA0025-3000	0.25	3	250
PFA0025-3500	0.25	3.5	250
PFA0025-4000	0.25	4	250
PFA0025-4500	0.25	4.5	250
PFA0025-5000	0.25	5	250