



Pillar Jib Crane Overbraced 270° Movable PFTMOB

Product information

Appropriate for an indoor or outdoor use, the beam of the PMT is built on an I beam profile. Its light weight gives it great flexibility for rotations of 270°. The structure of this jib crane is suitable for the optional installation of a hoist motor direction.

This jib crane is mounted on a movable concrete block provided. Displacement can be done by traveling crane (transport ring) or by forklift.

A full range of accessories is available.

Options

- Hoist power supply cable
- Lockable main switch
- Rotation slowing device
- Rotation stops to weld onto the assembly, or adjustable
- Single- or multipositions rotation lock
- Outdoor use
- Hot dip galvanizing (contact us)
- Electric or manual hoist

Part code	WLL ton	Length m	Cap. kg
6025PFTMOB015	0.15	2	150
PFTMOB0015-2500	0.15	2.5	150
PFTMOB0015-3000	0.15	3	150
PFTMOB0015-3500	0.15	3.5	150
PFTMOB0015-4000	0.15	4	150
PFTMOB0015-4500	0.15	4.5	150
PFTMOB0015-5000	0.15	5	150
PFTMOB0015-5500	0.15	5.5	150
PFTMOB0015-6000	0.15	6	150
6025PFTMOB025	0.25	2	250
PFTMOB0025-2500	0.25	2.5	250
PFTMOB0025-3000	0.25	3	250
PFTMOB0025-3500	0.25	3.5	250
PFTMOB0025-4000	0.25	4	250
PFTMOB0025-4500	0.25	4.5	250
PFTMOB0025-5000	0.25	5	250
6025PFTMOB050	0.5	2	500
PFTMOB0050-2500	0.5	2.5	500
PFTMOB0050-3000	0.5	3	500