MENNENS | Lifting Solutions Group
Axel Johnson International

Vertical Lifting Clamp IP10(J)

Product information



The Crosby IP10 (J) series vertical lifting clamps are designed for lifting, turning and transferring steel plates and similar materials. Available in four models for different jaw openings, material types and surface hardness levels, these clamps provide controlled handling with a 180° turning range and a locking mechanism for securing and releasing the load.

Best used for:

- Vertical lifting, turning and transferring steel plates in workshops and industrial operations.
- IP10 for standard steel with a surface hardness up to 363 HV10 (345 HB), IP10J for larger jaw openings, IP10S for stainless steel and IP10H for harder materials up to 472 HV10 (450 HB).

Product benefits:

- 180° turning range enables lifting, turning and repositioning of plates.
- Lock-open and lock-closed latch allows pretensioning and controlled release.
- Welded alloy steel body and forged components provide strength in a compact design.
- Individually proof tested to twice the WLL, with test certification supplied.
- Individual serial numbers and supplied documentation support traceability and inspection.

... *Read more*

Material: Alloy Steel.
Marking: According to standard, CE-mark, WLL, Logo, Type, Jaw opening, Serial number, Proof load test date
Temperature range: -40°C (-40°F) up to +100°C (+212°F)
Standard: EN 13155
Warning: A minimum load of 10% of the WLL is required. Except for WLL 500 kg which requires a minimum load of 5% of WLL.


Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Vertical Lifting Clamp IP10(J)

Blueprint



Technical data

Part code	WLL ton	Jaw width mm	Model	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	K mm	J mm	Weight kg
502100050160360	0.5	0-16	IP10	0-16	44	130	203	40	115	42	28	11	-	1.8
502100100200360	1	0-20	IP10	0-20	45	139	212	40	127	42	38	11	-	2.2
502100200350360	2	0-35	IP10	0-35	78	201	330	70	188	64	55	16	-	7.6
502100300400360	3	0-40	IP10	0-40	100	253	434	75	222	78	60	20	-	13.8
502100450400360	4.5	0-40	IP10	0-40	100	253	434	75	227	82	65	20	-	15
502100900500360	9	0-50	IP10	0-50	126	325	544	80	310	94	104	25	44	29.8
502101200540360	12	0-54	IP10	0-54	160	392	574	80	433	121	137	25	41	50.4
502101600640360	16	5-64	IP10	5-64	180	463	686	88	492	121	153	25	45	68
502102250800360	22.5	5-80	IP10	5-80	222	554	803	110	565	153	186	25	49	108
502103000800360	30	5-80	IP10	5-80	222	554	803	110	565	153	186	30	54	124

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved