

Swivel Eye / Eye Crosby S5

Product information



Design: Swivel with eyes equipped with tapered roller thrust bearing.

Features:

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided
- Other types and capacities up to 1250 t available on demand.

... [Read more](#)

Marking: CE-marked


Note: Always check before use if your steel wire rope is suitable for use with a swivel.

Warning: Not to be used on demolition- (wrecking-) balls!

Safety factor: 5:1

Swivel Eye / Eye Crosby S5

Blueprint



Technical data

Part code	WLL ton	Rope Ø mm	Swivel No	D, mm	G, mm	Qmm mm	Rmm mm	S mm	T mm	Weight kg
11.46297057	3	13	3-S-5	239	70	19.1	26.2	28.4	31.8	3.86
11.46297253	5	16	5-S-5	249	76	25.4	32.5	31.8	31.8	5.13
11.46297459	8.5	19	8-S-5	302	102	31.8	35.8	41.1	38.1	13.3
11.46297654	10	22	10-S-5	394	114	42.9	42.9	70	47.8	19.1
11.46297850	15	26	15-S-5	416	127	49.3	51.5	70	54	22.2
11.46298154	25	-	25-S-5	565	152	57	58.5	98.5	60.5	59
11.46298252	35	-	35-S-5	565	165	57	58.5	98.5	60.5	66
11.46298350	45	-	45-S-5	673	178	63.5	64.5	102	76	98