

Swivel Eye / Hook Crosby S6

Product information



Design: Swivel with eye and hook equipped with tapered roller thrust bearing.

Features:

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided
- All hooks furnished with latches
- Other types and capacities up to 1250 t available on demand.

... [Read more](#)

Marking: CE-marked


Note: Always check before use if your steel wire rope is suitable for use with a swivel.

Warning: Not to be used on demolition- (wrecking-) balls!

Safety factor: 5:1

Swivel Eye / Hook Crosby S6

Blueprint



Technical data

Part code	Diameter mm	WLL ton	Rope Ø mm	Swivel No	E mm	F mm	G mm	L mm	M mm	P mm	Q mm	R mm	S mm	T mm	V mm	Weight kg
11.46297066	-	3	13	3-S-6	292	123	70,0	38,9	35,8	36,6	19,1	26,2	28,4	31,8	28,4	4.23
11.46297262	-	5	16	5-S-6	332	160	76,0	49,3	42,9	46,0	25,4	32,5	31,8	31,8	36,6	6.46
11.46297468	0	8.5	19	8-S-6	408	192	102	62,5	56,5	57,0	31,8	35,8	41,1	38,1	41,1	14.5
11.46297663	-	10	22	10-S-6	486	212	114	66,0	61,0	66,0	42,9	42,9	70,0	47,8	49,3	20.6
11.46297869	-	15	26	15-S-6	540	263	127	71,5	61,0	76,0	49,3	51,5	70,0	54,0	60,5	28.6
11.46298163	-	25	-	25-S-6	699	346	152	87,5	92,0	93,0	57,0	58,5	98,5	60,5	76,0	61
11.46298261	-	35	-	35-S-6	780	357	165	98,5	95,5	116	57,0	58,5	98,5	60,5	81,0	98
11.46298369	-	45	-	45-S-6	907	392	178	121	108	129	63,5	64,5	102	76,0	82,5	122