



## Swivel Jaw End Crosby G-403

### Product information

Chain swivels with out bearing. According to Federal Specification RR-C-271F.

**Material:** Hot dip Galvanized - Quenched & Tempered

**Marking:** CE-marked, WLL

**Finish:** Galvanized

**Note:** The swivels are positioning devices and are not intended to rotate under load. For load swivels, see ball bearing swivels.

**Safety factor:** 5:1

| Part code    | Diameter mm | WLL ton | A mm | B mm | C mm | G mm | J mm | K mm | L    | M mm | N mm | P mm | R mm | U mm | V mm | Weight kg |
|--------------|-------------|---------|------|------|------|------|------|------|------|------|------|------|------|------|------|-----------|
| 11.451016411 | 8           | 0.57    | 41.4 | 20.6 | 25.4 | 20.6 | 20.6 | 12.7 | 28.7 | 9.7  | 22.4 | 7.9  | 74.5 | 52   | 46   | 0.15      |
| 11.451016439 | 10          | 1.02    | 51   | 23.9 | 31.8 | 25.4 | 25.4 | 16   | 35.8 | 12.7 | 26.9 | 9.7  | 92   | 63.5 | 57   | 0.3       |
| 11.451016457 | 13          | 1.63    | 63.5 | 33.3 | 38.1 | 33.3 | 33.3 | 19.1 | 44.5 | 16   | 33.3 | 12.7 | 114  | 81   | 73   | 0.61      |
| 11.451016475 | 16          | 2.36    | 76   | 39.5 | 44.5 | 41.4 | 38.1 | 23.9 | 52   | 19.1 | 38.1 | 16   | 135  | 98.5 | 87.5 | 1.12      |
| 11.451016493 | 19          | 3.27    | 89   | 44.5 | 51   | 47.8 | 47.8 | 28.7 | 64.5 | 22.4 | 44.5 | 19.1 | 154  | 109  | 102  | 1.76      |
| 11.451016518 | 22          | 4.54    | 102  | 52   | 57   | 54   | 54   | 34   | 70.9 | 25.4 | 52   | 22.4 | 178  | 127  | 115  | 2.66      |
| 11.451016536 | 25          | 5.67    | 114  | 58.5 | 63.5 | 67   | 60.5 | 44.5 | 94.5 | 28.7 | 71.5 | 28.7 | 217  | 146  | 151  | 4.46      |
| 11.451016572 | 32          | 8.16    | 145  | 68.5 | 79.5 | 79.5 | 76   | 52   | 109  | 41.4 | 71.5 | 35.1 | 248  | 179  | 162  | 7.14      |
| 11.451016590 | 38          | 20.5    | 178  | 98.5 | 102  | 143  | 102  | 73   | 152  | 57   | 113  | 57   | 362  | 254  | 275  | 24.8      |

## Blueprint

