

## Swivel Jaw End Crosby G-403

### Product information



Chain swivels with out bearing. According to Federal Specification RR-C-271F  
... [Read more](#)

**Material:** Hot dip Galvanized - Quenched & Tempered

**Marking:** CE-marked, WLL


**Finish:** Galvanized

**Note:** The swivels are positioning devices and are not intended to rotate under load.  
For load swivels, see ball bearing swivels.

**Safety factor:** 5:1

## Swivel Jaw End Crosby G-403

### Blueprint



### Technical data

| Part code    | Diameter mm | WLL ton | A mm | B mm | C mm | G, mm | J mm | K mm | L mm | Mmm mm | Nmm mm | Pmm mm | Rmm mm | U mm mm | V mm mm | Weight kg |
|--------------|-------------|---------|------|------|------|-------|------|------|------|--------|--------|--------|--------|---------|---------|-----------|
| 11.451016411 | 8           | 0.57    | 41.4 | 20.6 | 25.4 | 20.6  | 20.6 | 12.7 | 28.7 | 9.7    | 22.4   | 7.9    | 74.5   | 52      | 46      | 0.15      |
| 11.451016439 | 10          | 1.02    | 51   | 23.9 | 31.8 | 25.4  | 25.4 | 16   | 35.8 | 12.7   | 26.9   | 9.7    | 92     | 63.5    | 57      | 0.3       |
| 11.451016457 | 13          | 1.63    | 63.5 | 33.3 | 38.1 | 33.3  | 33.3 | 19.1 | 44.5 | 16     | 33.3   | 12.7   | 114    | 81      | 73      | 0.61      |
| 11.451016475 | 16          | 2.36    | 76   | 39.5 | 44.5 | 41.4  | 38.1 | 23.9 | 52   | 19.1   | 38.1   | 16     | 135    | 98.5    | 87.5    | 1.12      |
| 11.451016493 | 19          | 3.27    | 89   | 44.5 | 51   | 47.8  | 47.8 | 28.7 | 64.5 | 22.4   | 44.5   | 19.1   | 154    | 109     | 102     | 1.76      |
| 11.451016518 | 22          | 4.54    | 102  | 52   | 57   | 54    | 54   | 34   | 70.9 | 25.4   | 52     | 22.4   | 178    | 127     | 115     | 2.66      |
| 11.451016536 | 25          | 5.67    | 114  | 58.5 | 63.5 | 67    | 60.5 | 44.5 | 94.5 | 28.7   | 71.5   | 28.7   | 217    | 146     | 151     | 4.46      |
| 11.451016572 | 32          | 8.16    | 145  | 68.5 | 79.5 | 79.5  | 76   | 52   | 109  | 41.4   | 71.5   | 35.1   | 248    | 179     | 162     | 7.14      |
| 11.451016590 | 38          | 20.5    | 178  | 98.5 | 102  | 143   | 102  | 73   | 152  | 57     | 113    | 57     | 362    | 254     | 275     | 24.8      |