



## Solid Wire Rope Thimble Crosby S-412

### Product information

Fits pin for open wire rope socket, boom pendant clevis and wedge socket.

**Features:** Greater protection against wear and deformation of the wire rope eye giving longer service life.

**Material:** Cast Ductile Iron.

**Marking:** Manufacturer's symbol.

Part code	Rope Ø range mm	A	B mm	C mm	D mm	D tolerance	E mm	F mm	G mm	H mm	J mm	K mm	L	Weight kg
10.271037121	13	71.5	44.5	6.35	26.9	+5%	19.1	14.2	7.1	22.4	54	41.4	39.6	0.28
10.271037149	16	119	76	9.65	33.3	+4%	26.9	20.6	10.4	28.7	86	57	65	1
10.271037167	18-20	119	76	9.65	38.1	+3%	26.9	20.6	10.4	35.1	86	57	65	1.05
10.271037185	22	154	97	12.7	44.5	+3%	35.1	26.9	13.5	41.4	114	82.5	87.5	2.47
10.271037201	24-26	154	97	12.7	54	+3%	35.1	26.9	13.5	46	114	82.5	87.5	2.38
10.271037229	28-30	184	116	16	60.5	+2%	44.5	33.3	16.8	52.5	137	98.5	103	4.21
10.271037247	32-35	184	116	16	67	+2%	49.3	38.9	19.8	58.5	137	98.5	105	4.45

# Blueprint

