

Short Link Lifting Chain POWERTEX PSL Grade 8

Product information



The POWERTEX PSL Grade 8 Short Link Lifting Chain is a calibrated alloy steel lifting chain for building Grade 8 chain slings and chain lashings. Manufactured from quenched and tempered Grade 8 steel, each chain is calibrated, proof tested, and produced to EN 818-2, providing consistent dimensions, reliable performance, and full traceability for demanding industrial lifting applications. Also usable for grade 8 lashing systems acc. to EN 12195-3.

Best used for:

- Building Grade 8 chain slings
- Chain lashings requiring calibrated short link lifting chain
- Industrial lifting applications where EN 818-2 compliant chain is required
- Load lashing systems grade 8 according to EN 12195-3

Not ideal for:

- Applications requiring higher lifting capacity or lower product weight, where Grade 10 or Grade 12 chain may be a better choice.

Product benefits

- Calibrated links ensure accurate assembly with compatible Grade 8 components
- Every chain link is proof load tested 2.5xWLL before delivery for verified quality
- Production batches are tested to meet minimum breaking force requirements
- Quenched and tempered Grade 8 alloy steel combines high strength with ductile behaviour
- Minimum 20% elongation before failure helps absorb overload without brittle fracture
- Automatic chain welding delivers consistent dimensions and manufacturing quality

Click on the link below to learn more about the POWERTEX PSL Grade 8 Short Link Lifting Chain. [... Read more](#)

Material: Quenched and Tempered Alloy Steel of Grade 8 quality (EN 818-2)

Marking: According to standard, CE-marked, UKCA-marked, Factory symbol, Grade 8, Traceability batch code marking

Temperature range: -40°C up to +200°C without reduction of WLL. Up to 400°C with reduction acc. to standard.

Finish: Black electrophoretic paint (RAL 9005).


Standard: EN 818-2, AS 2321, ASTM A391/A391M

Safety factor: 4:1

Grade: 8

Short Link Lifting Chain POWERTEX PSL Grade 8

Blueprint



Technical data

Chain diameter mm	WLL ton	Min. breaking force kN	Proof Load kN	d mm	p mm	W1 mm	W2 mm	Weight kg/m
6	1.12	45.2	28.3	6	18	7.8	22.2	0.8
8	2	80.6	50.3	8	24	10.92	29.6	1.5
10	3.15	126	78.5	10	30	13	37	2.3
13	5.3	214	133	13	39	17.48	48.1	3.9
16	8	322	201	16	48	20.8	59.2	5.8
20	12.5	504	314	20	60	26	74	8.9