

# Webbing Sling Endura

## Product information

**Design:** Flat woven, colour coded slings with folded soft eyes. For heavy duty use.

**Stretch with working load:** 2-3%.

**Length tolerance:** Nominal length  $\pm 3\%$ .

**Standard:** EN 1492-1

**Material:** Polyester. Resistant to most acids but not to strong alkalis.

**Marking:** CE-marked, The slings are provided with a blue label with manufacturer's symbol, working load limit (WLL), length, CE marking and a label with handling instructions.

**Temperature range:** Approx. -40°C - +100°C.

**Safety factor:** 7:1.

Code	WLL ton	EWL m	Webbing width mm	Colour
ENDHB30	1	1	30	violet
ENDHB30	1	1.5	30	violet
ENDHB30	1	2	30	violet
ENDHB30	1	2.5	30	violet
ENDHB30	1	3	30	violet
ENDHB30	1	4	30	violet
ENDHB30	1	5	30	violet

ENDHB30	1	6	30	violet
ENDHB30	1	-	30	violet
ENDHB60	2	1	60	Green
ENDHB60	2	1.5	60	Green
ENDHB60	2	2	60	Green
ENDHB60	2	2.5	60	Green
ENDHB60	2	3	60	Green
ENDHB60	2	4	60	Green
ENDHB60	2	5	60	Green
ENDHB60	2	6	60	Green
ENDHB60	2	-	60	Green
ENDHB90	3	1	90	Yellow
ENDHB90	3	1.5	90	Yellow
ENDHB90	3	2	90	Yellow
ENDHB90	3	2.5	90	Yellow
ENDHB90	3	3	90	Yellow
ENDHB90	3	4	90	Yellow
ENDHB90	3	5	90	Yellow
ENDHB90	3	6	90	Yellow
ENDHB90	3	-	90	Yellow
ENDHB120	4	1	120	Grey
ENDHB120	4	1.5	120	Grey
ENDHB120	4	2	120	Grey

ENDHB120	4	2.5	120	Grey
ENDHB120	4	3	120	Grey
ENDHB120	4	4	120	Grey
ENDHB120	4	5	120	Grey
ENDHB120	4	6	120	Grey
ENDHB120	4	-	120	Grey
ENDHB150	5	1	150	Red
ENDHB150	5	1.5	150	Red
ENDHB150	5	2	150	Red
ENDHB150	5	2.5	150	Red
ENDHB150	5	3	150	Red
ENDHB150	5	4	150	Red
ENDHB150	5	5	150	Red
ENDHB150	5	6	150	Red
ENDHB150	5	-	150	Red