



VARI Pump S - 400V - 1 stage

Product information

Holmatro Vari Pump units

To control your hydraulic system, Holmatro offers a various range of pump units:

- 230V, 400V or petrol driven
- 1 or 2 stage

Unique specifications:

- In case of a power failure, the oil pressure is maintained
- Protected against pressure drop by pressure-controlled non-return valve
- Excluding single-acting (M311) or double-acting (M322 or M323) control valve
- TIP: If you want to create flexibility for feature use; ad a Sada switch (M304) to your pump set-up
- You want to make sure you choose the right vari-pump for your application? Download the Holmatro Vari pump configurator.

Additional information:

- To have a safe and controlled system, assemble your vari-pump with advised components:
- Option A: 1 cylinder application : assemble a pressure gauge directly on the pump unit
- Option B: multiple cylinder application: add a flow panel & assembly set to your pump set-up
- TIP: download the vari-pump configurator for more info

Why add a pressure gauge or flowpanel?

- To measure the pressure in the system; safety first
- Go here for the valves & accessories for Holmatro vari pumps

Also available:

- Hydraulic cylinders 700 bar
- Hydraulic hoses 700bar
- System components to complete your hydraulic system
- Other hydraulic pump units 700bar to control the cylinder(s)

To be added:

Safety sheet cylinders = PDF/Download

Features: - Safe; in case of a power failure, the oil pressure is maintained.

Note: Excluding single-acting or double-acting control valve.

Code	Max. working pressure bar/Mpa	oil capacity cc	Engine	L mm	W mm	H mm	Weight kg
12 S 12 E	720 / 72	12,000	400 VAC-1.5 kW-50 Hz-3 PH	400	300	541	43
12 S 6 SE	720 / 72	6,000	400 VAC-1.5 kW-50 Hz-3 PH	400	300	441	35
18 S 25 E	720 / 72	25,000	400 VAC-2.2 kW-50 Hz-3 PH	500	380	541	64
18 S 50 E	720 / 72	50,000	400 VAC-2.2 kW-50 Hz-3 PH	500	380	676	94