

Hydraulic Hoses - Standard Hoses - H SOU

Product information



Holmatro Standard hoses

- Suitable for high pressure hydraulics / max 700bar working pressure
- Anti-kink spring on both sides
- All hoses are individually tested during the production proces.
- Safety factor 4:1
- 6 year max. lifespan.

Standard supplied with:

- Hose connection A = 3/8" NPT male
- Hose connection B = A 119 male coupler
- Already filled with oil.

Also available:

- Hydraulic cylinders
- Hydraulic pump units 700bar to control the cylinder(s)
- System components to complete your hydraulic system

Available on request:

- Different lengths.
- Other colour.

Safety factor: 4:1

Code	Size	Model	Max. working pressure bar/Mpa	connection A	connection B
H 1 SOU	1 m	H 1 SOU	720 / 72	3/8" NPT male	coupler A 119
H 10 SOU	10 m	H 10 SOU	720 / 72	3/8" NPT male	coupler A 119
H 2 SOU	2 m	H 2 SOU	720 / 72	3/8" NPT male	coupler A 119
H 3 SOU	3 m	H 3 SOU	720 / 72	3/8" NPT male	coupler A 119
H 5 SOU	5 m	H 5 SOU	720 / 72	3/8" NPT male	coupler A 119