

## Lifting Eye FP

---

### Product information



Enormously flat lifting eye.

- The eyes can be loaded with working load limit in all directions and rotates 360°.
- Automatic locking link when folded.
- Secured four times against breakage in all load directions.
- Admissible working range of take-up link 110°.

... [Read more](#)

---

**Material:** Eye and swivel of alloy steel.

**Marking:** CE-marked, UKCA-marked, WLL.


**Finish:** Painted.

**Note:** The surface that the lifting eyes shall be attached to shall be flat and tolerate the load it is going to be exposed to.

**Safety factor:** 4:1

## Lifting Eye FP

### Blueprint



### Technical data

Part code	Code	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	Ø d mm mm	E mm	F mm	G, mm	Imm mm	Øs mm mm	Weight kg
11.420381100000	FP 0.5	0.5	M10	40	69	50	48	13	28	100	12	52	34	0.71
11.420381101000	FP 0.8	0.8	M12	65	69	50	48	13	28	100	17	51	34	0.73
11.420381101500	FP 1.5	1.5	M16	160	69	50	48	13	28	100	27	49	34	0.77
11.420381102000	FP 2.5	2.5	M20	420	69	50	48	13	33	103	37	44	41	0.92
11.420381104000	FP 4	4	M24	750	104	76	78	18	39	147	41	74	58	2.5
11.420381104200	FP 4-S	4	M24	750	69	50	48	13	34	103	46	40	41	1.05
11.420381105000	FP 5	5	M27	1,000	104	76	72	18	39	147	51	72	58	2.63
11.420381106000	FP 6	6	M30	1,400	104	76	72	18	39	147	51	70	58	2.74
11.420381108000	FP 8	8	M36	1,800	104	76	72	18	43	147	57	62	58	3.15