

Chain Sling CSX-175 Grade 10

Product information



Design: Chain sling with master link on one end and clevis load hook on the other end.

∅ 26 mm chain is fitted with an eye hook. Other combinations possible on demand.

Dimensions: ∅ 6–26 mm (other dimensions on demand).

[... Read more](#)

Material: Alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40°C up to 200°C (up to 380° possible on demand)

Standard: EN 818-4

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

Chain Sling CSX-175 Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m
11.91CSX17506XXX	6	1.4	-
11.91CSX17506005	6	1.4	0.5
11.91CSX17506010	6	1.4	1
11.91CSX17506015	6	1.4	1.5
11.91CSX17506020	6	1.4	2
11.91CSX17506030	6	1.4	3
11.91CSX17506040	6	1.4	4
11.91CSX17506050	6	1.4	5
11.91CSX17506060	6	1.4	6
11.91CSX17508XXX	8	2.5	-
11.91CSX17508005	8	2.5	-
11.91CSX17508010	8	2.5	-
11.91CSX17508015	8	2.5	-
11.91CSX17508020	8	2.5	-
11.91CSX17508030	8	2.5	-
11.91CSX17508040	8	2.5	-
11.91CSX17508050	8	2.5	-
11.91CSX17508060	8	2.5	-
11.91CSX17510XXX	10	4	-
11.91CSX17510005	10	4	-
11.91CSX17510010	10	4	-
11.91CSX17510015	10	4	-
11.91CSX17510020	10	4	-
11.91CSX17510030	10	4	-
11.91CSX17510040	10	4	-
11.91CSX17510050	10	4	-
11.91CSX17510060	10	4	-
11.91CSX17513XXX	13	6.7	-
11.91CSX17513005	13	6.7	-
11.91CSX17513010	13	6.7	-
11.91CSX17513015	13	6.7	-

Chain Sling CSX-175 Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m
11.91CSX17513020	13	6.7	-
11.91CSX17513030	13	6.7	-
11.91CSX17513040	13	6.7	-
11.91CSX17513050	13	6.7	-
11.91CSX17513060	13	6.7	-
11.91CSX17516XXX	16	10	-
11.91CSX17516005	16	10	-
11.91CSX17516010	16	10	-
11.91CSX17516015	16	10	-
11.91CSX17516020	16	10	-
11.91CSX17516030	16	10	-
11.91CSX17516040	16	10	-
11.91CSX17516050	16	10	-
11.91CSX17516060	16	10	-
11.91CSX17519XXX	19	14	-
11.91CSX17519005	19	14	-
11.91CSX17519010	19	14	-
11.91CSX17519015	19	14	-
11.91CSX17519020	19	14	-
11.91CSX17519030	19	14	-
11.91CSX17519040	19	14	-
11.91CSX17519050	19	14	-
11.91CSX17519060	19	14	-
11.91CSX17522XXX	22	19	-
11.91CSX17522005	22	19	-
11.91CSX17522010	22	19	-
11.91CSX17522015	22	19	-
11.91CSX17522020	22	19	-
11.91CSX17522030	22	19	-
11.91CSX17522040	22	19	-
11.91CSX17522060	22	19	-

Chain Sling CSX-175 Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m
11.91CSX17526XXX	26	26.5	-
11.91CSX17526005	26	26.5	-
11.91CSX17526010	26	26.5	-
11.91CSX17526015	26	26.5	-
11.91CSX17526020	26	26.5	-
11.91CSX17526030	26	26.5	-
11.91CSX17526040	26	26.5	-
11.91CSX17526050	26	26.5	-
11.91CSX17526060	26	26.5	-