



Chain Sling CSX-175 Grade 10

Product information

Design: Chain sling with master link on one end and clevis load hook on the other end. \varnothing 26 mm chain is fitted with an eye hook. Other combinations possible on demand.

Dimensions: \varnothing 6–26 mm (other dimensions on demand).

Material: Alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40°C up to 200°C (up to 380° possible on demand)

Standard: EN 818-4

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	EWL m
11.91CSX17506XXX	6	1.4	-
11.91CSX17506005	6	1.4	0.5
11.91CSX17506010	6	1.4	1
11.91CSX17506015	6	1.4	1.5
11.91CSX17506020	6	1.4	2
11.91CSX17506030	6	1.4	3
11.91CSX17506040	6	1.4	4

11.91CSX17506050	6	1.4	5
11.91CSX17506060	6	1.4	6
11.91CSX17508XXX	8	2.5	-
11.91CSX17508005	8	2.5	-
11.91CSX17508010	8	2.5	-
11.91CSX17508015	8	2.5	-
11.91CSX17508020	8	2.5	-
11.91CSX17508030	8	2.5	-
11.91CSX17508040	8	2.5	-
11.91CSX17508050	8	2.5	-
11.91CSX17508060	8	2.5	-
11.91CSX17510XXX	10	4	-
11.91CSX17510005	10	4	-
11.91CSX17510010	10	4	-
11.91CSX17510015	10	4	-
11.91CSX17510020	10	4	-
11.91CSX17510030	10	4	-
11.91CSX17510040	10	4	-
11.91CSX17510050	10	4	-
11.91CSX17510060	10	4	-
11.91CSX17513XXX	13	6.7	-
11.91CSX17513005	13	6.7	-
11.91CSX17513010	13	6.7	-

11.91CSX17513015	13	6.7	-
11.91CSX17513020	13	6.7	-
11.91CSX17513030	13	6.7	-
11.91CSX17513040	13	6.7	-
11.91CSX17513050	13	6.7	-
11.91CSX17513060	13	6.7	-
11.91CSX17516XXX	16	10	-
11.91CSX17516005	16	10	-
11.91CSX17516010	16	10	-
11.91CSX17516015	16	10	-
11.91CSX17516020	16	10	-
11.91CSX17516030	16	10	-
11.91CSX17516040	16	10	-
11.91CSX17516050	16	10	-
11.91CSX17516060	16	10	-
11.91CSX17519XXX	19	14	-
11.91CSX17519005	19	14	-
11.91CSX17519010	19	14	-
11.91CSX17519015	19	14	-
11.91CSX17519020	19	14	-
11.91CSX17519030	19	14	-
11.91CSX17519040	19	14	-
11.91CSX17519050	19	14	-

11.91CSX17519060	19	14	-
11.91CSX17522XXX	22	19	-
11.91CSX17522005	22	19	-
11.91CSX17522010	22	19	-
11.91CSX17522015	22	19	-
11.91CSX17522020	22	19	-
11.91CSX17522030	22	19	-
11.91CSX17522040	22	19	-
11.91CSX17522060	22	19	-
11.91CSX17526XXX	26	26.5	-
11.91CSX17526005	26	26.5	-
11.91CSX17526010	26	26.5	-
11.91CSX17526015	26	26.5	-
11.91CSX17526020	26	26.5	-
11.91CSX17526030	26	26.5	-
11.91CSX17526040	26	26.5	-
11.91CSX17526050	26	26.5	-
11.91CSX17526060	26	26.5	-