

Chain Sling CSX-275 Grade 10

Product information



Design: Chain sling with master link on one end and clevis load hook on the other end of each leg.

∅ 26 mm chain is fitted with eye hooks. Other combinations possible on demand.

Dimensions: ∅ 6–26 mm (other dimensions on demand).

... [Read more](#)

Material: Alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40°C up to 200°C (up to 380° possible on demand)

Standard: EN 818-4

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

Chain Sling CSX-275 Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m
11.91CSX27506XXX	6	2	-
11.91CSX27506005	6	2	0.5
11.91CSX27506010	6	2	1
11.91CSX27506015	6	2	1.5
11.91CSX27506020	6	2	2
11.91CSX27506030	6	2	3
11.91CSX27506040	6	2	4
11.91CSX27506050	6	2	5
11.91CSX27506060	6	2	6
11.91CSX27508XXX	8	3.55	-
11.91CSX27508005	8	3.55	0.5
11.91CSX27508010	8	3.55	1
11.91CSX27508015	8	3.55	1.5
11.91CSX27508020	8	3.55	2
11.91CSX27508030	8	3.55	3
11.91CSX27508040	8	3.55	4
11.91CSX27508050	8	3.55	5
11.91CSX27508060	8	3.55	6
11.91CSX27510XXX	10	5.6	-
11.91CSX27510005	10	5.6	0.5
11.91CSX27510010	10	5.6	1
11.91CSX27510015	10	5.6	1.5
11.91CSX27510020	10	5.6	2
11.91CSX27510030	10	5.6	3
11.91CSX27510040	10	5.6	4
11.91CSX27510050	10	5.6	5
11.91CSX27510060	10	5.6	6
11.91CSX27513XXX	13	9.5	-
11.91CSX27513005	13	9.5	0.5
11.91CSX27513010	13	9.5	1
11.91CSX27513015	13	9.5	1.5

Chain Sling CSX-275 Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m
11.91CSX27513020	13	9.5	2
11.91CSX27513030	13	9.5	3
11.91CSX27513040	13	9.5	4
11.91CSX27513050	13	9.5	5
11.91CSX27513060	13	9.5	6
11.91CSX27516XXX	16	14	-
11.91CSX27516005	16	14	0.5
11.91CSX27516010	16	14	1
11.91CSX27516015	16	14	1.5
11.91CSX27516020	16	14	2
11.91CSX27516030	16	14	3
11.91CSX27516040	16	14	4
11.91CSX27516050	16	14	5
11.91CSX27516060	16	14	6
11.91CSX27519XXX	19	20	-
11.91CSX27519005	19	20	0.5
11.91CSX27519010	19	20	1
11.91CSX27519015	19	20	1.5
11.91CSX27519020	19	20	2
11.91CSX27519030	19	20	3
11.91CSX27519040	19	20	4
11.91CSX27519050	19	20	5
11.91CSX27519060	19	20	6
11.91CSX27522XXX	22	26.5	-
11.91CSX27522005	22	26.5	0.5
11.91CSX27522010	22	26.5	1
11.91CSX27522015	22	26.5	1.5
11.91CSX27522020	22	26.5	2
11.91CSX27522030	22	26.5	3
11.91CSX27522040	22	26.5	4
11.91CSX27522050	22	26.5	5

Chain Sling CSX-275 Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m
11.91CSX27522060	22	26.5	6
11.91CSX27526XXX	26	37.5	-
11.91CSX27526005	26	37.5	0.5
11.91CSX27526010	26	37.5	1
11.91CSX27526015	26	37.5	1.5
11.91CSX27526020	26	37.5	2
11.91CSX27526030	26	37.5	3
11.91CSX27526040	26	37.5	4
11.91CSX27526050	26	37.5	5
11.91CSX27526060	26	37.5	6