

## Chain Sling CSX-375 Grade 10

### Product information

**Design:** Chain sling with master link on one end and clevis load hook on the other end of each leg.  $\varnothing$  26 mm chain is fitted with eye hooks. Other combinations possible on demand.

**Dimensions:**  $\varnothing$  6–26 mm (other dimensions on demand).

**Material:** Alloy steel.

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to 200°C (up to 380° possible on demand)

**Standard:** EN 818-4

**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 10



Part code	Chain diameter mm	WLL ton	EWL m
11.91CSX37506XXX	6	3	-
11.91CSX37506005	6	3	0.5
11.91CSX37506010	6	3	1
11.91CSX37506015	6	3	1.5
11.91CSX37506020	6	3	2
11.91CSX37506030	6	3	3
11.91CSX37506040	6	3	4
11.91CSX37506050	6	3	5
11.91CSX37506060	6	3	6
11.91CSX37508XXX	8	5.3	-

11.91CSX37508005	8	5.3	0.5
11.91CSX37508010	8	5.3	1
11.91CSX37508015	8	5.3	1.5
11.91CSX37508020	8	5.3	2
11.91CSX37508030	8	5.3	3
11.91CSX37508040	8	5.3	4
11.91CSX37508050	8	5.3	5
11.91CSX37508060	8	5.3	6
11.91CSX37510XXX	10	8	-
11.91CSX37510005	10	8	0.5
11.91CSX37510010	10	8	1
11.91CSX37510015	10	8	1.5
11.91CSX37510020	10	8	2
11.91CSX37510030	10	8	3
11.91CSX37510040	10	8	4
11.91CSX37510050	10	8	5
11.91CSX37510060	10	8	6
11.91CSX37513XXX	13	14	-
11.91CSX37513005	13	14	0.5
11.91CSX37513010	13	14	1
11.91CSX37513015	13	14	1.5
11.91CSX37513020	13	14	2
11.91CSX37513030	13	14	3
11.91CSX37513040	13	14	4
11.91CSX37513050	13	14	5
11.91CSX37513060	13	14	6

11.91CSX37516XXX	16	21.2	-
11.91CSX37516005	16	21.2	0.5
11.91CSX37516010	16	21.2	1
11.91CSX37516015	16	21.2	1.5
11.91CSX37516020	16	21.2	2
11.91CSX37516030	16	21.2	3
11.91CSX37516040	16	21.2	4
11.91CSX37516050	16	21.2	5
11.91CSX37516060	16	21.2	6
11.91CSX37519XXX	19	30	-
11.91CSX37519005	19	30	0.5
11.91CSX37519010	19	30	1
11.91CSX37519015	19	30	1.5
11.91CSX37519020	19	30	2
11.91CSX37519030	19	30	3
11.91CSX37519040	19	30	4
11.91CSX37519050	19	30	5
11.91CSX37519060	19	30	6
11.91CSX37522XXX	22	40	-
11.91CSX37522005	22	40	0.5
11.91CSX37522010	22	40	1
11.91CSX37522015	22	40	1.5
11.91CSX37522020	22	40	2
11.91CSX37522030	22	40	3
11.91CSX37522040	22	40	4
11.91CSX37522050	22	40	5

11.91CSX37522060	22	40	6
11.91CSX37526005	26	56	0.5
11.91CSX37526010	26	56	1
11.91CSX37526015	26	56	1.5
11.91CSX37526020	26	56	2
11.91CSX37526030	26	56	3
11.91CSX37526040	26	56	4
11.91CSX37526050	26	56	5
11.91CSX37526060	26	56	6
11.91CSX37526XXX	26	56	-