



## Chain Sling CSX-475 Grade 10

### Product information

**Design:** Chain sling with master link on one end and clevis load hook on the other end of each leg.  $\varnothing$  26 mm chain is fitted with eye hooks. Other combinations possible on demand.

**Dimensions:**  $\varnothing$  6–26 mm (other dimensions on demand).

**Material:** Alloy steel.

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to 200°C (up to 380° possible on demand)

**Standard:** EN 818-4

**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 10

| Part code        | Chain diameter<br>mm | WLL<br>ton | EWL<br>m |
|------------------|----------------------|------------|----------|
| 11.91CSX47506XXX | 6                    | 3          | -        |
| 11.91CSX47506005 | 6                    | 3          | 0.5      |
| 11.91CSX47506010 | 6                    | 3          | 1        |
| 11.91CSX47506015 | 6                    | 3          | 1.5      |
| 11.91CSX47506020 | 6                    | 3          | 2        |
| 11.91CSX47506030 | 6                    | 3          | 3        |
| 11.91CSX47506040 | 6                    | 3          | 4        |
| 11.91CSX47506050 | 6                    | 3          | 5        |

|                  |    |     |     |
|------------------|----|-----|-----|
| 11.91CSX47506060 | 6  | 3   | 6   |
| 11.91CSX47508XXX | 8  | 5.3 | -   |
| 11.91CSX47508005 | 8  | 5.3 | 0.5 |
| 11.91CSX47508010 | 8  | 5.3 | 1   |
| 11.91CSX47508015 | 8  | 5.3 | 1.5 |
| 11.91CSX47508020 | 8  | 5.3 | 2   |
| 11.91CSX47508030 | 8  | 5.3 | 3   |
| 11.91CSX47508040 | 8  | 5.3 | 4   |
| 11.91CSX47508050 | 8  | 5.3 | 5   |
| 11.91CSX47508060 | 8  | 5.3 | 6   |
| 11.91CSX47510XXX | 10 | 8   | -   |
| 11.91CSX47510005 | 10 | 8   | 0.5 |
| 11.91CSX47510010 | 10 | 8   | 1   |
| 11.91CSX47510015 | 10 | 8   | 1.5 |
| 11.91CSX47510020 | 10 | 8   | 2   |
| 11.91CSX47510030 | 10 | 8   | 3   |
| 11.91CSX47510040 | 10 | 8   | 4   |
| 11.91CSX47510050 | 10 | 8   | 5   |
| 11.91CSX47510060 | 10 | 8   | 6   |
| 11.91CSX47513XXX | 13 | 14  | -   |
| 11.91CSX47513005 | 13 | 14  | 0.5 |
| 11.91CSX47513010 | 13 | 14  | 1   |
| 11.91CSX47513015 | 13 | 14  | 1.5 |

|                  |    |      |     |
|------------------|----|------|-----|
| 11.91CSX47513020 | 13 | 14   | 2   |
| 11.91CSX47513030 | 13 | 14   | 3   |
| 11.91CSX47513040 | 13 | 14   | 4   |
| 11.91CSX47513050 | 13 | 14   | 5   |
| 11.91CSX47513060 | 13 | 14   | 6   |
| 11.91CSX47516XXX | 16 | 21.2 | -   |
| 11.91CSX47516005 | 16 | 21.2 | 0.5 |
| 11.91CSX47516010 | 16 | 21.2 | 1   |
| 11.91CSX47516015 | 16 | 21.2 | 1.5 |
| 11.91CSX47516020 | 16 | 21.2 | 2   |
| 11.91CSX47516030 | 16 | 21.2 | 3   |
| 11.91CSX47516040 | 16 | 21.2 | 4   |
| 11.91CSX47516050 | 16 | 21.2 | 5   |
| 11.91CSX47516060 | 16 | 21.2 | 6   |
| 11.91CSX47519XXX | 19 | 30   | -   |
| 11.91CSX47519005 | 19 | 30   | 0.5 |
| 11.91CSX47519010 | 19 | 30   | 1   |
| 11.91CSX47519015 | 19 | 30   | 1.5 |
| 11.91CSX47519020 | 19 | 30   | 2   |
| 11.91CSX47519030 | 19 | 30   | 3   |
| 11.91CSX47519040 | 19 | 30   | 4   |
| 11.91CSX47519050 | 19 | 30   | 5   |
| 11.91CSX47519060 | 19 | 30   | 6   |

|                  |    |    |     |
|------------------|----|----|-----|
| 11.91CSX47522XXX | 22 | 40 | -   |
| 11.91CSX47522005 | 22 | 40 | 0.5 |
| 11.91CSX47522010 | 22 | 40 | 1   |
| 11.91CSX47522015 | 22 | 40 | 1.5 |
| 11.91CSX47522020 | 22 | 40 | 2   |
| 11.91CSX47522030 | 22 | 40 | 3   |
| 11.91CSX47522040 | 22 | 40 | 4   |
| 11.91CSX47522050 | 22 | 40 | 5   |
| 11.91CSX47522060 | 22 | 40 | 6   |
| 11.91CSX47526005 | 26 | 56 | 0.5 |
| 11.91CSX47526010 | 26 | 56 | 1   |
| 11.91CSX47526015 | 26 | 56 | 1.5 |
| 11.91CSX47526020 | 26 | 56 | 2   |
| 11.91CSX47526030 | 26 | 56 | 3   |
| 11.91CSX47526040 | 26 | 56 | 4   |
| 11.91CSX47526050 | 26 | 56 | 5   |
| 11.91CSX47526060 | 26 | 56 | 6   |
| 11.91CSX47526XXX | 26 | 56 | -   |