

Chain Sling CSX-475 Grade 10

Product information



Design: Chain sling with master link on one end and clevis load hook on the other end of each leg.

ø 26 mm chain is fitted with eye hooks. Other combinations possible on demand.

Dimensions: Ø 6–26 mm (other dimensions on demand).

[... Read more](#)

Material: Alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40°C up to 200°C (up to 380° possible on demand)

Standard: EN 818-4

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

Chain Sling CSX-475 Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m
11.91CSX47506XXX	6	3	-
11.91CSX47506005	6	3	0.5
11.91CSX47506010	6	3	1
11.91CSX47506015	6	3	1.5
11.91CSX47506020	6	3	2
11.91CSX47506030	6	3	3
11.91CSX47506040	6	3	4
11.91CSX47506050	6	3	5
11.91CSX47506060	6	3	6
11.91CSX47508XXX	8	5.3	-
11.91CSX47508005	8	5.3	0.5
11.91CSX47508010	8	5.3	1
11.91CSX47508015	8	5.3	1.5
11.91CSX47508020	8	5.3	2
11.91CSX47508030	8	5.3	3
11.91CSX47508040	8	5.3	4
11.91CSX47508050	8	5.3	5
11.91CSX47508060	8	5.3	6
11.91CSX47510XXX	10	8	-
11.91CSX47510005	10	8	0.5
11.91CSX47510010	10	8	1
11.91CSX47510015	10	8	1.5
11.91CSX47510020	10	8	2
11.91CSX47510030	10	8	3
11.91CSX47510040	10	8	4
11.91CSX47510050	10	8	5
11.91CSX47510060	10	8	6
11.91CSX47513XXX	13	14	-
11.91CSX47513005	13	14	0.5
11.91CSX47513010	13	14	1
11.91CSX47513015	13	14	1.5

Chain Sling CSX-475 Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m
11.91CSX47513020	13	14	2
11.91CSX47513030	13	14	3
11.91CSX47513040	13	14	4
11.91CSX47513050	13	14	5
11.91CSX47513060	13	14	6
11.91CSX47516XXX	16	21.2	-
11.91CSX47516005	16	21.2	0.5
11.91CSX47516010	16	21.2	1
11.91CSX47516015	16	21.2	1.5
11.91CSX47516020	16	21.2	2
11.91CSX47516030	16	21.2	3
11.91CSX47516040	16	21.2	4
11.91CSX47516050	16	21.2	5
11.91CSX47516060	16	21.2	6
11.91CSX47519XXX	19	30	-
11.91CSX47519005	19	30	0.5
11.91CSX47519010	19	30	1
11.91CSX47519015	19	30	1.5
11.91CSX47519020	19	30	2
11.91CSX47519030	19	30	3
11.91CSX47519040	19	30	4
11.91CSX47519050	19	30	5
11.91CSX47519060	19	30	6
11.91CSX47522XXX	22	40	-
11.91CSX47522005	22	40	0.5
11.91CSX47522010	22	40	1
11.91CSX47522015	22	40	1.5
11.91CSX47522020	22	40	2
11.91CSX47522030	22	40	3
11.91CSX47522040	22	40	4
11.91CSX47522050	22	40	5

Chain Sling CSX-475 Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m
11.91CSX47522060	22	40	6
11.91CSX47526005	26	56	0.5
11.91CSX47526010	26	56	1
11.91CSX47526015	26	56	1.5
11.91CSX47526020	26	56	2
11.91CSX47526030	26	56	3
11.91CSX47526040	26	56	4
11.91CSX47526050	26	56	5
11.91CSX47526060	26	56	6
11.91CSX47526XXX	26	56	-