

Chain Sling CSX-476 Grade 10

Product information



Design: Chain sling with master link on one end and clevis safety hook on the other end of each leg.

Ø 19 and 22 mm chain are fitted with eye safety hooks. Other combinations possible on demand.

Dimensions: Ø 6–22 mm (other dimensions on demand).

[... Read more](#)

Material: Alloy steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to 200°C (up to 380° possible on demand)

Standard: EN 818-4

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

Chain Sling CSX-476 Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m
11.91CSX47606XXX	6	3	-
11.91CSX47606005	6	3	0.5
11.91CSX47606010	6	3	1
11.91CSX47606015	6	3	1.5
11.91CSX47606020	6	3	2
11.91CSX47606030	6	3	3
11.91CSX47606040	6	3	4
11.91CSX47606050	6	3	5
11.91CSX47606060	6	3	6
11.91CSX47608XXX	8	5.3	-
11.91CSX47608005	8	5.3	0.5
11.91CSX47608010	8	5.3	1
11.91CSX47608015	8	5.3	1.5
11.91CSX47608020	8	5.3	2
11.91CSX47608030	8	5.3	3
11.91CSX47608040	8	5.3	4
11.91CSX47608050	8	5.3	5
11.91CSX47608060	8	5.3	6
11.91CSX47610XXX	10	8	-
11.91CSX47610005	10	8	0.5
11.91CSX47610010	10	8	1
11.91CSX47610015	10	8	1.5
11.91CSX47610020	10	8	2
11.91CSX47610030	10	8	3
11.91CSX47610040	10	8	4
11.91CSX47610050	10	8	5
11.91CSX47610060	10	8	6
11.91CSX47613XXX	13	14	-
11.91CSX47613005	13	14	0.5
11.91CSX47613010	13	14	1
11.91CSX47613015	13	14	1.5

Chain Sling CSX-476 Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m
11.91CSX47613020	13	14	2
11.91CSX47613030	13	14	3
11.91CSX47613040	13	14	4
11.91CSX47613050	13	14	5
11.91CSX47613060	13	14	6
11.91CSX47616XXX	16	21.2	-
11.91CSX47616005	16	21.2	0.5
11.91CSX47616010	16	21.2	1
11.91CSX47616015	16	21.2	1.5
11.91CSX47616020	16	21.2	2
11.91CSX47616030	16	21.2	3
11.91CSX47616040	16	21.2	4
11.91CSX47616050	16	21.2	5
11.91CSX47616060	16	21.2	6
11.91CSX47619XXX	19	30	-
11.91CSX47619005	19	30	0.5
11.91CSX47619010	19	30	1
11.91CSX47619015	19	30	1.5
11.91CSX47619020	19	30	2
11.91CSX47619030	19	30	3
11.91CSX47619040	19	30	4
11.91CSX47619050	19	30	5
11.91CSX47619060	19	30	6
11.91CSX47622XXX	22	40	-
11.91CSX47622005	22	40	0.5
11.91CSX47622010	22	40	1
11.91CSX47622015	22	40	1.5
11.91CSX47622020	22	40	2
11.91CSX47622030	22	40	3
11.91CSX47622040	22	40	4
11.91CSX47622050	22	40	5

Chain Sling CSX-476 Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m
11.91CSX47622060	22	40	6