



## Master Link A/S Grade 10

### Product information

Designed for use in 1-leg and 2-leg slings.

**Material:** Alloy steel.

**Marking:** According to standard, CE-marked, code and grade.

**Finish:** Violet powder coated.

**Standard:** EN 1677-4

**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 10

Part code	Code	Chain diameter mm	WLL ton	EWL mm	dmm mm	t mm	w mm mm	smm mm	Weight kg
11.021262	A/S-13-10	6-7	2.3	110	13	110	60	10	0.34
11.021255	A/S-16-10	8	3.5	110	17	110	60	14	0.55
11.021256	A/S-18-10	10	5	135	19	135	75	14	0.94
11.021257	A/S-22-10	13	7.6	160	23	160	90	17	1.64
11.021258	A/S-26-10	16	10	180	27	180	100	20	2.53
11.021259	A/S-32-10	19	14	200	33	200	110	26	4.28
11.021260	A/S-36-10	22	25.1	260	36	260	140	-	6.22
11.0270046	A/S-45-10	26	30.8	340	45	340	180	-	12.74
11.0270050	A/S-50-10	26	40	350	50	350	190	-	16.55

## Blueprint

